

**MEGHALAYA BASIN DEVELOPMENT AUTHORITY  
(MBDA)**

**Protection of Vulnerable Catchment Areas in Meghalaya (MegARISE)**

Financed under

German Financial Cooperation with India

**BMZ-Nos. 2015 67 643(Loan) and 2015 67 650 (Grant)**

**REQUEST FOR QUOTATION**

**for**

**Procurement of Material for Knowledge Management under MegARISE**

**RfQ No.: MBDA/MegARISE/2025-26/G-17/**

**Procurement No:** G17

Date of Issue: 10<sup>th</sup> December 2025

## Table of Contents

Section I: Letter of Invitation .....	3
Section II: Pre-selected Firms.....	7
Section III: Instructions to Bidders.....	8
Section IV: Eligibility Criteria.....	13
Section IV a - KfW Policy – Sanctionable Practice – Social and Environmental Responsibility .....	14
Section V: Declaration of Undertaking.....	16
Section VI: Form of Quotation .....	21
Section VII: Schedule of Requirements.....	22
Section VIII: Price Schedule of Goods.....	23
Section IX: Schedule of Technical Specifications of Goods .....	24
Section X: Conditions of Contract.....	84
Section XI: Contract Form.....	91

## Section I: Letter of Invitation

### Procurement of Material for Knowledge Management under MegARISE

**RFQ No.: MBDA/MegARISE/2025-26/G-17/**

**Date:** 10<sup>th</sup> December 2025

Dear Sir/Madam,

1. The Government of Meghalaya hereinafter called “Meghalaya Basin Development Authority (MBDA)”, has received financing from KfW towards the cost of the “Protection of Vulnerable Catchment Areas in Meghalaya” Project, hereinafter called “MegARISE”, and intends to apply part of the proceeds towards eligible payments under the contract for which this Request for Quotation (RFQ) is issued.
2. Meghalaya Basin Development Authority (MBDA) now invites sealed price quotations from eligible suppliers (refer to Section III. Clause No. 3 for eligibility criteria) for the supply and delivery of the following items mentioned in the table below:

**Table 1:**

Lot #	Item	Quantity	EMD Amount	Past experience
1	Camera	Camera Body 1	2	41,000/-
		Camera Body 2	2	
		Camera Bag type 1	1	
		Camera Bag type 2	2	
		360 action cam with accessories	6	
		Handheld action camera with accessories	1	
2	Battery	Camera Battery	12	7,000/-
		Battery Grip	4	
		Rechargeable AA battery ( pack of 4) with charger	1	
		Powerbank	4	
3	Storage	960 TB CFexpress 4.0 Type A Memory Card	4	13,000/-
		480 TB CFexpress 4.0 Type A Memory Card	4	
		512GB UHS-II microSDXC Memory Card with SD Adapter	7	
		CFexpress® Type A Reader	2	
		SSD External hard drive 4TB	2	
4	Lens	Zoom Lens - 24–70 mm F2.8 GM II	4	53,000/-
		Prime Lens - 85mm f/1.2	2	
		Macro : 90 mm F2.8 Macro G OSS	1	
		Wide angle Lens - FE 12–24 mm F2.8 GM	2	

Lot #	Item	Quantity	EMD Amount	Past experience
	Telephoto Lens - Super telephoto Zoom 100-400mm G Master lens	1		
	Telephoto Lens - 50–150 mm F2 GM	1		
	Telephoto Lens - 70-200mm f/2.8 VR S LENS	1		
5	Filter (ND) s Neutral Density Polarizer Filter	82mm Size 77mm Size 95mm Size	4 4 1	3500/-
5	Rear filter for wide lens:	Rear filter for wide lens:	2	
6	Microphone	Lavelier mics Shotgun mics	2 2	2000/-
7	Tripod	Tripod type 1 Tripod type 2 Gorillapod Tripod for CMU	2 2 2 2	6000/-
8	Light	Video Light Powerbank holder for video light Diffuser Box Lightstand Speedlight flash for respective camera system Speedlight diffuser kit Speedlight Battery Speed light trigger	3 3 3 3 1 1 2 1	4,000/-
9	Accessories	Camera Cage Gimbal with accessories Screen Protector POV Chest Mount Utility Frame USB C Power delivery Cable Storage unit for Gear 3.5mm In ear earphones Camera cleaning Kit	2 2 6 6 6 4 2 2 4	11,000/-

3. Quotations must be in a sealed envelope for both price and technical offer, clearly marked with the inscription:

**“Procurement of Material for Knowledge Management under MegARISE”**  
**RFQ No.: MBDA/MegARISE/2025-26/G-17/**

**Addressed to:**

**Meghalaya Basin Development Authority (MBDA)**

**Procurement Division**  
**RDL Building, 3rd Floor,**  
**Springside Opposite HP Office**  
**Lumsohphoh, Nongthymmai – 793014**

4. The deadline for receipt of your sealed quotation is **05<sup>th</sup> January 2026 by 1600 Hrs.** (IST). Quotations will be opened on **05<sup>th</sup> January 2026 by 1630 Hrs.** All late submissions will be rejected outright.
5. All bids must be accompanied by the following documents. Offers with incomplete documents will be rejected:
  - a) Declaration of Undertaking (Section V)
  - b) Form of Quotation (Section VI)
  - c) List of Goods and Price Schedule (Section VIII)
  - d) Schedule of Technical Specifications of Goods Offered (Section IX)
  - e) A copy of company's business registration/trading license
  - f) GST Registration Certificate
  - g) Manufacturers or Technical Brochures (catalogues) on the items offered
  - h) Non-Manufacturers' Bidders will submit the Manufacturer's Authorization Form (MAF).
  - i) Copies of Past Contract/Supply orders/completion certificate as mentioned in the document.
  - j) Bidders shall submit an Earnest Money Deposit (EMD) in favor of MegARISE, MBDA, in the form of an account payee demand draft or bank guarantee, valid for a minimum period of three (3) months. The EMD of unsuccessful bidders will be returned without interest after finalization of the tender. The EMD of the successful bidder will be retained and released without interest upon successful completion of the contract. In the event that the EMD submitted by the successful bidder expires before the completion of the contract, the bidder shall renew the EMD or submit a fresh one to ensure continuous validity until contract closure.
6. Tenderers are required to complete the quotation Form and Price Schedule on their company's letter head in the formats provided in Section VI and VIII of the bid documents.
7. Quotation shall be fixed and presented in Indian Rupees. Price Quotations shall indicate any discount separately. The financial evaluation will be based on the price quotation per item. The final financial evaluation will consider the economically most advantageous offer for all items.
- 8. Price quotations will indicate all applicable taxes separately.**
9. Tenders shall be valid for **sixty (60) days** from the last date of tender submission.
10. Tenderers are requested to bid for any of the lots.
11. The items shall be delivered to the Recipient within **30 days** from the date of Contract Signature.
12. 100% payment of the contract price will be paid within thirty (30) days after full delivery of all the items and accepted by the Purchaser and the Recipient.

13. A Tender Security or Insurance bond is not required.
14. When preparing their quotations, tenderers shall be guided by the Instructions and Conditions of supply in Section III.
15. Requests for clarifications shall be submitted within five (5) days after the date of Issuing of the Invitation of Quotation to the address: [kfwmbdaprocurement@gmail.com](mailto:kfwmbdaprocurement@gmail.com)
16. We look forward to receiving your quotation and thank you for your interest in the project.

Yours sincerely

*Sd/-*  
**Additional Project Director**  
**MegARISE, MBDA**

## **Section II: Pre-selected Firms**

**Not Applicable**

### Section III: Instructions to Bidders

#### Procurement of Material for Knowledge Management under MegARISE

RFQ No.: MBDA/MegARISE/2025-26/G-17/

<b>1. Rules of the procurement</b>	<p>The rules of this procurement and the selection of the firm for the supply of the goods will be made in accordance with the KfW "Guidelines for the Procurement of Consulting Services, Works, Plant, Goods and Non-Consulting Services in Financial Cooperation with Partner Countries".</p> <p>The latest version of these KfW Guidelines can be downloaded from KfW's website under:</p> <p><a href="https://www.kfw-entwicklungsbank.de/PDF/Download-Center/PDF-Dokumente-Richtlinien/Vergaberichtlinien-2019-Englisch-Internet_2.pdf">https://www.kfw-entwicklungsbank.de/PDF/Download-Center/PDF-Dokumente-Richtlinien/Vergaberichtlinien-2019-Englisch-Internet_2.pdf</a></p>
<b>2. Context of the requirement</b>	<b>Procurement of Material for Knowledge Management under MegARISE</b>

<p><b>3. Eligibility criteria to participate in public procurement</b></p>	<p>The suppliers established in India shall:</p> <ul style="list-style-type: none"> <li>a.) be in conformity with the provisions of the law and</li> <li>b.) have fulfilled their obligations with regard to the payment of duties and taxes and</li> <li>c.) are generally eligible as per KfW Eligibility Criteria (Section IV).</li> <li>d.) have no conflict of interest as per article 1.3.3 of KfW's Procurement Guidelines. In particular</li> <li>e.) not being owned or controlled by the purchaser;</li> <li>f.) not having business or family relationship with Purchaser's staff involved in the procurement process or the supervision of the resulting contract;</li> <li>g.) not being associated with the firm that prepared the design, and specifications of the contract that is subject of this procurement;</li> <li>h.) not having the same legal representative as another bidder.</li> <li>i.) shall observe the highest standard of ethics and respect social as well environmental standards during the procurement process and contract implementation as set forth in Section IV a – KfW Policy Sanctionable Practice – Social and Environmental Responsibility. KfW will reject a proposal for award, and will impose sanctions on parties involved, if it determines that the bidder recommended for award or any other party, has engaged in corrupt, fraudulent, collusive, or coercive practices in competing for, or in executing, the Contract.</li> <li>j.) The bidder must have successfully executed at least one supply order for similar items to any Government Department or PSU in Meghalaya within the last three years, up to <b>31st October 2025</b>. A copy of the relevant supply order must be submitted along with the quotation.</li> </ul> <p>For the avoidance of doubt, it is hereby clarified that if a bidder submits a bid for multiple lots, the bidder must provide a separate supply order for each respective lot. Accordingly, if a bidder submits a bid for three lots, three corresponding supply orders must be submitted one for each lot. This criteria is applicable for all the Lots i.e from 1-15.</p> <p>k.) With regards to the supply and delivery kindly note the following:</p> <p>All the Goods and Related Services to be supplied under the contract and financed by KfW shall have their origin in any country in accordance with Section IV-KfW Eligibility Criteria</p>
<p><b>4. Pre-selected firms</b></p>	<p>N/A</p>
<p><b>5. Clarifications</b></p>	<p>Requests for clarifications shall be submitted within five (5) working days after the date of issuing of this RFQ to <a href="mailto:kfwmbdaprourement@gmail.com">kfwmbdaprourement@gmail.com</a></p>

<b>6. Submission of quotation</b>	<p>Quotations shall be submitted in 1 original quotation enclosed in a sealed envelope, clearly marked with the inscription:</p> <p><b>“Procurement of Material for Knowledge Management under MegARISE “</b></p> <p><b>RfQ No: MBDA/MegARISE/2025-26/G-17/</b></p> <p>and must be sent or delivered to the address:</p> <p><b>Meghalaya Basin Development Authority (MBDA) Procurement Division RDL Building, 3rd Floor, Springside Opposite HP Office Lumsohphoh, Nongthymmai – 793014</b></p>
<b>7. Submission deadline for the quotation</b>	<p><b>Date: No later than 05<sup>th</sup> January 2026 by 1600 Hrs.</b></p> <p>Any quotations received after the deadline prescribed in this section will be rejected and returned unopened to the bidder.</p>
<b>8. Opening of quotations</b>	<p>The opening will be held on <b>05<sup>th</sup> January 2026 at 1630 Hrs.</b> at Meghalaya Basin Development Authority (MBDA), Procurement Division, RDL Building, 3rd Floor, Springside Opposite HP Office, Lumsohphoh, Nongthymmai – 793014, office in the presence of the Bid Evaluation Committee and the bidders' representatives who prefer to attend.</p>
<b>9. Period of validity of quotation</b>	<p>60 Days (starting from submission date)</p>
<b>10. Documents comprising the quotation</b>	<p><b>Each bidder shall submit only one quotation.</b></p> <p>Quotations submitted by the bidders shall comprise the following documents:</p> <ul style="list-style-type: none"> <li>a.) Declaration of Undertaking (Section V)</li> <li>b.) Form of Quotation (Section VI)</li> <li>c.) List of Goods and Price Schedule (Section VIII)</li> <li>d.) Schedule of Technical Specifications of Goods Offered (Section IX)</li> <li>e.) Company's Business registration/trading license</li> <li>f.) GST Registration Certificate</li> <li>g.) Manufacturer's or Technical Brochures (catalogues) on the items offered</li> <li>h.) Non-Manufacturer Bidders will submit the Manufacturer's Authorization Form (MAF).</li> <li>i.) Copies of past contracts/supply orders/completion certificates as mentioned in the <b>Table I</b></li> </ul> <p><b>Incomplete offers will be rejected.</b></p>
<b>11. Brief description of the required goods (Technical details in Section IX)</b>	<p>As per <b>Table 1</b></p>

<b>12. Language of bid</b>	The bid prepared by the Bidder, and all correspondence and documents relating to the bid exchanged by the Bidder and the Purchaser, shall be written in the English language.
<b>13. Currency of quotation</b>	<input checked="" type="checkbox"/> Indian Rupee (INR) ₹
<b>14. Bid prices</b>	<ul style="list-style-type: none"> <li>The Bidder shall indicate, on the appropriate Price Schedule attached to these documents (Section VIII), the total Bid Price quoted CIP (Carriage and Insurance Paid To) for goods, transport and insurance to the named place of destination (specified in No. 23), excluding the custom duties and other import taxes already paid (need to be supported with documentary evidence) or to be paid on the goods already imported.</li> <li>The prices indicated in the quotation are fixed and not subject to any adjustment during the period of validity.</li> <li>In case of any discrepancy between the unit price and the total price (obtained by multiplying the unit price and quantity), the unit price shall prevail and the total price shall be corrected.</li> </ul>
<b>15. Taxes on price quotation</b>	<p>Quotation must be <b>exclusive</b> of any Taxes.</p> <p>Applicable taxes shall be quoted separately.</p> <p>Expenditure Claims under the Project will be exclusive of taxes and will be borne by the MBDA.</p>
<b>16. Partial quotations</b>	<input type="checkbox"/> Not permitted (quotations must include all lots in this RFQ) <input checked="" type="checkbox"/> Permitted (quotations can exclude some lots in this RFQ)
<b>17. Clarification of quotations</b>	The Purchaser may, at its discretion, ask any Bidder for a clarification of its quotation, if necessary.
<b>18. Correction of arithmetical errors</b>	Provided that the quotation is substantially responsive, the Purchaser shall correct arithmetical errors on the basis that the respective unit price and amount expressed in words shall prevail.
<b>19. Evaluation criteria</b>	<ul style="list-style-type: none"> <li>A quotation is considered substantially responsive if it meets the requirements listed in No. 10 without material deviation, reservation, or omission. Non-responsive offers will be rejected.</li> <li>The <u>technical evaluation</u> shall be carried out by an evaluation of compliance to confirm that all requirements of Section IX: Technical Specifications have been met without any material deviation or reservation, or omission.</li> <li>The <u>financial evaluation</u> will be the lowest price evaluation of the total price of the offer (corrected as necessary) after the evaluation of the technical compliance of the bids.</li> <li>The financial evaluation will be evaluated on the net prices without the GST rate. Financial evaluation will be conducted lot-wise. The bidder offering the lowest price for each lot will be awarded the contract for that lot.</li> </ul>
<b>20. Award of contract</b>	<ul style="list-style-type: none"> <li>The Purchaser will award the Contract to the successful Bidder whose bid has been determined to be administratively and technical compliant and has been determined as the lowest evaluated bid.</li> </ul>

<b>21. Notification of award</b>	<ul style="list-style-type: none"> <li>• Prior to the expiration of the period of bid validity, the Purchaser shall notify the successful Bidder, in writing, that its Bid has been accepted.</li> <li>• Until a formal Contract is prepared and executed, the notification of award shall constitute a binding Contract.</li> </ul>
<b>22. Signing contract</b>	<ul style="list-style-type: none"> <li>• At the time as the Purchaser notifies the successful Bidder that his bid has been accepted, the Purchaser will send the Bidder the Contract Form provided in this RFQ Document, incorporating all agreements between the parties.</li> <li>• Within seven (7) days of receipt of the Contract Form, the successful Bidder shall sign and date the Contract and return it to the Purchaser. The contract will become effective only upon return of the signed Contract Agreement.</li> </ul>
<b>23. Recipient and delivery location of goods</b>	<p>Recipient of goods:</p> <p><b>Address:</b> Meghalaya Basin Development (MBDA)  <b>Procurement Division</b>  <b>RDL Building, 3rd Floor,</b>  <b>Springside Opposite HP Office</b>  <b>Lumsohphoh, Nongthymmai – 793014</b>  <b>Email:</b> <a href="mailto:kfwmbdaprocurement@gmail.com">kfwmbdaprocurement@gmail.com</a></p>

## Section IV: Eligibility Criteria

### Eligibility in KfW-Financed Procurement

1. Consulting Services, Works, Goods, Plant and Non-Consulting Services are eligible for KfW financing regardless of the country of origin of the Contractors (including Subcontractors and suppliers for the execution of the Contract), except where an international embargo or sanction by the United Nations, the European Union or the German Government applies.
2. Applicants/Bidders (including all members of a Joint Venture and proposed or engaged Subcontractors) shall not be awarded a KfW-financed Contract if, on the date of submission of their Application/Offer or on the intended date of Award of a Contract, they:
  - 2.1. are bankrupt or being wound up or ceasing their activities, are having their activities administered by courts, have entered into receivership, or are in any analogous situation;
  - 2.2. have been
    - (a) convicted by a final judgement or a final administrative decision or subject to financial sanctions by the United Nations, the European Union and/or the German Government for involvement in a criminal organization, money laundering, terrorist-related offences, child labour or trafficking in human beings; this criterion of exclusion is also applicable to legal Persons, whose majority of shares are held or factually controlled by natural or legal Persons which themselves are subject to such convictions or sanctions;
    - (b) convicted by a final court decision or a final administrative decision by a court, the European Union or national authorities in the Partner Country or in Germany for Sanctionable Practice during any Tender Process or the performance of a Contract or for an irregularity affecting the EU's financial interests, unless they provide supporting information together with their Declaration of Undertaking (Form available as Appendix to the Application/Offer which shows that this conviction is not relevant in the context of this Contract and that adequate compliance measures have been taken in reaction;
  - 2.3. have been subject within the past five years to a Contract termination fully settled against them for significant or persistent failure to comply with their contractual obligations during Contract performance, unless this termination was challenged, and the dispute resolution is still pending or has not confirmed a full settlement against them;
  - 2.4. have not fulfilled applicable fiscal obligations regarding payments of taxes either in the country where they are constituted or the PEA's country;
  - 2.5. are subject to an exclusion decision of the World Bank or any other multilateral development bank and are listed in the respective table with debarred and cross-debarred firms and individual available on the World Bank's website or any other multilateral development bank unless they provide supporting information together with their Declaration of Undertaking which shows that this exclusion is not relevant in the context of this Contract or
  - 2.6. have given misrepresentation in documentation requested by the PEA as part of the Tender Process of the relevant Contract.
  3. State-owned entities may compete only if they can establish that they (i) are legally and financially autonomous, and (ii) operate under commercial law. To be eligible, a state-owned entity shall establish to KfW's satisfaction, through all relevant documents, including its charter and other information KfW may request, that it: (i) is a legal entity separate from their state (ii) does not currently receive substantial subsidies or budget support; (iii) operates like any commercial enterprise, and, *inter alia*, is not obliged to pass on its surplus to their state, can acquire rights and liabilities, borrow funds and be liable for repayment of its debts, and can be declared bankrupt.

## **Section IV a - KfW Policy – Sanctionable Practice – Social and Environmental Responsibility**

### **1) Sanctionable Practice**

The PEA and the Contractors (including all members of a Joint Venture and proposed or engaged Subcontractors) must observe the highest standard of ethics during the Tender Process and performance of the Contract.

By signing the Declaration of Undertaking the Contractors declare that (i) they did not and will not engage in any Sanctionable Practice likely to influence the Tender Process and the corresponding Award of Contract to the PEA's detriment, and that (ii) in case of being awarded a Contract they will not engage in any Sanctionable Practice.

Moreover, KfW requires to include in the Contracts a provision pursuant to which Contractors must permit KfW and in case of financing by the European Union also to European institutions having competence under European law to inspect the respective accounts, records and documents relating to the Tender Process and the performance of the Contract, and to have them audited by auditors appointed by KfW.

KfW reserves the right to take any action it deems appropriate to check that these ethics rules are observed and reserves, in particular, the rights to:

- (a) reject an Offer for Award of Contract if during the Tender Process the Bidder who is recommended for the Award of Contract has engaged in Sanctionable Practice, directly or by means of an agent in view of being awarded the Contract;
- (b) declare misprocurement and exercise its rights on the ground of the Funding Agreement with the PEA relating to suspension of disbursements, early repayment and termination if, at any time, the PEA, Contractors or their legal representatives or Subcontractors have engaged in Sanctionable Practice during the Tender Process or performance of the Contract without the PEA having taken appropriate action in due time satisfactory to KfW to remedy the situation, including by failing to inform KfW at the time they knew of such practices.

KfW defines, for the purposes of this provision, the terms set forth below as follows:

<b>Coercive Practice</b>	The impairing or harming, or threatening to impair or harm, directly or indirectly, any person or the property of the person with a view to influencing improperly the actions of a person.
<b>Collusive Practice</b>	An arrangement between two or more persons designed to achieve an improper purpose, including influencing improperly the actions of another person.
<b>Corrupt Practice</b>	The promising, offering, giving, making, insisting on, receiving, accepting or soliciting, directly or indirectly, of any illegal payment or undue advantage of any nature, to or by any person, with the intention of influencing the actions of any person or causing any person to refrain from any action.
<b>Fraudulent Practice</b>	Any action or omission, including misrepresentation that knowingly or recklessly misleads, or attempts to mislead, a person to obtain a financial benefit or to avoid an obligation.
<b>Obstructive Practice</b>	Means (i) deliberately destroying, falsifying, altering or concealing evidence material to the investigation or the making of false statements to investigators, in order to materially impede an official investigation into allegations of a Corrupt Practice, Fraudulent Practice, Coercive Practice or Collusive Practice, or threatening, harassing or intimidating any Person to prevent them from disclosing their knowledge of matters relevant to the investigation or from pursuing the investigation, or (ii) any act intended to materially impede the exercise of KfW's access to

contractually required information in connection with an official investigation into allegations of a Corrupt Practice, Fraudulent Practice, Coercive Practice or Collusive Practice.

<b>Sanctionable Practice</b>	Any Coercive Practice, Collusive Practice, Corrupt Practice, Fraudulent Practice or Obstructive Practice (as such terms are defined herein) which is unlawful under the Financing Agreement.
------------------------------	--

## **2) Social and Environmental Responsibility**

Projects financed in whole or partly in the framework of Financial Cooperation have to ensure compliance with international Environmental, Social, Health and Safety (ESHS) standards (including issues of sexual exploitation and abuse and gender based violence) Contractors in KfW-financed projects shall consequently undertake in the respective Contracts to:

- a) comply with and ensure that all their Subcontractors and major suppliers, i.e. for major supply items comply with international environmental and labour standards, consistent with applicable law and regulations in the country of implementation of the respective Contract and the fundamental conventions of the International Labour Organisation<sup>1</sup> (ILO) and international environmental treaties and;
- b) implement any environmental and social risks mitigation measures, as identified in the environmental and social impact assessment (ESIA) and further detailed in the environmental and social management plan (ESMP) as far as these measures are relevant to the Contract and implement measures for the prevention of sexual exploitation and abuse and gender-based violence.

---

<sup>1</sup> In case ILO conventions have not been fully ratified or implemented in the Employer's country the Applicant/Bidder/Contractor shall, to the satisfaction of the Employer and KfW, propose and implement appropriate measures in the spirit of the said ILO conventions with respect to a) workers grievances on working conditions and terms of employment, b) child labour, c) forced labour, d) worker's organisations and e) non-discrimination.

## Section V: Declaration of Undertaking

### Declaration of Undertaking

Reference name of the Application/Offer/Contract: **("Contract")<sup>2</sup>**  
To: **("Project Executing Agency")**

1. We recognise and accept that KfW only finances projects of the Project Executing Agency ("PEA")<sup>3</sup> subject to its own conditions which are set out in the Funding Agreement it has entered into with the PEA. As a matter of consequence, no legal relationship exists between KfW and our company, our Joint Venture or our Subcontractors under the Contract. The PEA retains exclusive responsibility for the preparation and implementation of the Tender Process and the performance of the Contract.
2. We hereby certify that neither we nor any of our board members or legal representatives nor any other member of our Joint Venture including Subcontractors under the Contract are in any of the following situations:
  - 2.1) being bankrupt, wound up or ceasing our activities, having our activities administered by courts, having entered into receivership, reorganisation or being in any analogous situation;
  - 2.2) having been convicted by a final judgment or a final administrative decision or a preliminary investigation/charge is pending against us for involvement in a criminal organisation, money laundering, terrorist-related offences, child labour or trafficking in human beings, or have been subject to (financial) sanctions and/or embargo provisions by the United Nations, the European Union or the Federal Republic of Germany. This exclusion criterion is also applicable to legal persons whose shares (or the majority thereof) are owned or de facto controlled by natural or legal persons against whom such judgments, administrative decisions, (financial) sanctions and/or embargoes have been imposed and – in the case of (financial) sanctions and/or embargoes – these restrictive measures continue to apply;
  - 2.3) having been convicted by a final court decision or a final administrative decision by a court, the European Union, national authorities in the Partner Country or in Germany for Sanctionable Practice in connection with a Tender Process or the performance of a Contract or for an irregularity affecting the EU's financial interests (*in the event of such a conviction, the Applicant or Bidder shall attach to this Declaration of Undertaking supporting information showing that this conviction is not relevant in the context of this Contract and that adequate compliance measures have been taken in reaction*);
  - 2.4) having been subject within the past five years to a Contract termination fully settled against us for significant or persistent failure to comply with our contractual obligations during such Contract performance, unless this termination was challenged and dispute resolution is still pending or has not confirmed a full settlement against us;
  - 2.5) not having fulfilled the applicable fiscal obligations with regard to the payment of taxes at the respective tax residence and in the country of origin of the PEA (*contractors based in Annex 1 countries (<https://www.consilium.europa.eu/de/policies/eu-list-of-non-cooperative-jurisdictions>) must submit a fully completed and legally countersigned declaration of tax conformity (Appendix 1 to the Declaration of Undertaking) in addition to the Declaration of Undertaking at the time of award of the contract/contract review. This shall become an integral part of the contract. Failure to submit may result in exclusion from the awarding procedure. For contractors based in countries not listed as Annex 1 countries, only the Declaration of Undertaking must be submitted, and not the declaration of tax conformity*);

<sup>2</sup> Capitalised terms used, but not otherwise defined in this Declaration of Undertaking have the meaning given to such term in KfW's "Guidelines for the Procurement of Consulting Services, Works, Plant, Goods and Non-Consulting Services in Financial Cooperation with Partner Countries".

<sup>3</sup> The PEA means the purchaser, the employer, the client, as the case may be, for the procurement of Consulting Services, Works, Plant, Goods or Non-Consulting Services.

- 2.6) being subject to an exclusion decision of the World Bank or any other multilateral development bank and being listed on the website <http://www.worldbank.org/debarr> or respectively on the relevant list of any other multilateral development bank (*in the event of such exclusion, the Applicant or Bidder shall attach to this Declaration of Undertaking supporting information showing that this exclusion is not relevant in the context of this Contract and that adequate compliance measures have been taken in reaction*); or
- 2.7) being guilty of misrepresentation in supplying the information required as a condition of participation in the Tender.

3. We hereby certify that neither we, nor any of the members of our Joint Venture or any of our Subcontractors under the Contract are in any of the following situations of conflict of interest:

- 3.1) being an affiliate controlled by the PEA or a shareholder controlling the PEA, unless the stemming conflict of interest has been brought to the attention of KfW and resolved to its satisfaction;
- 3.2) having a business or family relationship with a PEA's staff involved in the Tender Process or the supervision of the resulting Contract, unless the stemming conflict of interest has been brought to the attention of KfW and resolved to its satisfaction;
- 3.3) being controlled by or controlling another Applicant or Bidder, or being under common control with another Applicant or Bidder, or receiving from or granting subsidies directly or indirectly to another Applicant or Bidder, having the same legal representative as another Applicant or Bidder, maintaining direct or indirect contacts with another Applicant or Bidder which allows us to have or give access to information contained in the respective Applications or Offers, influencing them or influencing decisions of the PEA;
- 3.4) being engaged in a Consulting Services activity, which, by its nature, may be in conflict with the assignments that we would carry out for the PEA;
- 3.5) in the case of procurement of Works, Plant or Goods:
  - i. having prepared or having been associated with a Person who prepared specifications, drawings, calculations and other documentation to be used in the Tender Process of this Contract;
  - ii. having been recruited (or being proposed to be recruited) ourselves or any of our affiliates, to carry out works supervision or inspection for this Contract;

4. If we are a state-owned entity, and compete in a Tender Process, we certify that we have legal and financial autonomy and that we operate under commercial laws and regulations.

5. We undertake to bring to the attention of the PEA, which will inform KfW, any change in situation with regard to points 2 to 4 here above.

6. In the context of the Tender Process and performance of the corresponding Contract:

- 6.1) neither we nor any of the members of our Joint Venture nor any of our Subcontractors under the Contract have engaged or will engage in any Sanctionable Practice, or violate the Guidelines during the Tender Process and in the case of being awarded a Contract will engage in any Sanctionable Practice during the performance of the Contract;
- 6.2) neither we nor any of the members of our Joint Venture or any of our Subcontractors under the Contract shall acquire or supply any equipment nor operate in any sectors under an embargo of the United Nations, the European Union or Germany; and
- 6.3) we commit ourselves to complying with and ensuring that our Subcontractors and major suppliers under the Contract comply with international environmental and labour standards, consistent with laws and regulations applicable in the country of implementation of the Contract and the fundamental conventions of the International

Labour Organisation<sup>4</sup> (ILO) and international environmental treaties. Moreover, we shall implement environmental and social risks mitigation measures when specified in the relevant environmental and social management plans or other similar documents provided by the PEA and, in any case, implement measures to prevent sexual exploitation and abuse and gender-based violence.

7. In the case of being awarded a Contract, we, as well as all members of our Joint Venture partners and Subcontractors under the Contract will, (i) upon request, provide information relating to the Tender Process and the performance of the Contract and (ii) permit the PEA and KfW or an agent appointed by either of them, and in the case of financing by the European Union also to European institutions having competence under European Union law, to inspect the respective accounts, records and documents, to permit on-the-spot checks and to ensure access to sites and the respective project.
8. In the case of being awarded a Contract, we, as well as all our Joint Venture partners and Subcontractors under the Contract undertake to preserve above mentioned records and documents in accordance with applicable law, but in any case, for at least six years from the date of fulfillment or termination of the Contract. Our financial transactions and financial statements shall be subject to auditing procedures in accordance with applicable law. Furthermore, we accept that our data (including personal data) generated in connection with the preparation and implementation of the Tender Process and the performance of the Contract are stored and processed according to the applicable law by the PEA and KfW.

Name: \_\_\_\_\_ In the capacity of: \_\_\_\_\_

Duly empowered to sign in the name and on behalf of<sup>5</sup>: \_\_\_\_\_

Signature: \_\_\_\_\_ Dated: \_\_\_\_\_

---

4 In case ILO conventions have not been fully ratified or implemented in the Employer's country the Applicant/Bidder/Contractor shall, to the satisfaction of the Employer and KfW, propose and implement appropriate measures in the spirit of the said ILO conventions with respect to a) workers grievances on working conditions and terms of employment, b) child labour, c) forced labour, d) worker's organisations and e) non-discrimination.

5 In the case of a JV, insert the name of the JV. The person who will sign the application, bid or proposal on behalf of the Applicant/Bidder shall attach a power of attorney from the Applicant/Bidder.

**Declaration of tax conformity – binding confirmation for legal persons**

**Name of company**

I hereby confirm with my signature that:

1. I am authorised to make this declaration on behalf of the above company;
2. the company properly pays all taxes in accordance with the tax laws of the country in which the company is domiciled;
3. the company is not currently nor has been in the past involved in any legal proceedings concerning the taxation of the company;
4. the company will duly pay taxes that may arise from the provision of contracted services;
5. all information and statements provided in advance are complete, accurate in terms of content and currently correct.

.....

(Place)

.....

(Date)

.....

(Name of the consultant)

.....

(Signature(s))

**Declaration of tax conformity – binding confirmation for natural persons**

I hereby confirm with my signature that:

1. I make this declaration in my name/on my own account;
2. I duly pay taxes that I am obliged to pay under the tax law of my country of residence;
3. I am not currently involved in tax law court proceedings, nor have I been in the past;
4. I will duly pay taxes that may arise from the provision of contracted services;
5. I have filled in all the information and statements of this confirmation in full, accurately in terms of content and that they are up to date at this time.

.....

.....

.....

(Place)

(Date)

(Name of the person)

.....

(Signature)

## **Section VI: Form of Quotation**

*[The Bidder shall prepare his Bid Submission Form on a letterhead paper specifying the Bidder's complete name, address and communication details].*

Date: \_\_\_\_\_

To: **Meghalaya Basin Development Authority (MBDA)**

**Ref.: Procurement of Material for Knowledge Management under MegARISE**

**RFQ No.: MBDA/MegARISE/2025-26/G-17/**

We refer to your RFQ No. \_\_\_\_\_ dated \_\_\_\_\_. We undertake to supply the goods as indicated in the attached Schedule of Technical Specifications and List of Goods and Price Schedule in accordance with the Request for Quotation document for the contract price of \_\_\_\_\_ (amount in words and figures) in \_\_\_\_\_ (name of currency).

We confirm that the prices quoted in the List of Goods and Price Schedule are fixed and firm for the duration of the validity period and will not be subject to revision or variation.

We undertake to complete the delivery of the above equipment to the Recipient within \_\_\_\_ days from the date of Contract Signature.

We confirm that we are eligible to participate in public procurement and meet the eligibility criteria specified in the Section III Clause No. 3

The validity period of our quotation is: \_\_\_\_\_ days.

Until a formal Contract is prepared and executed, this quotation, together with your written acceptance thereof and your notification of award, shall constitute a binding Contract between us. We understand that you are not bound to accept the lowest or any Quotation you receive.

We hereby confirm that this Quotation complies with the validity of the Quotation required by the documents.

Authorized Signature: \_\_\_\_\_

Name and Title of Signatory: \_\_\_\_\_

## **Section VII: Schedule of Requirements**

### **1) Supply of Goods & warranty:**

Each item of equipment to be supplied is described in Section IX: Schedule of Technical Specifications of Goods. The successful Supplier shall supply a copy of manufacturer's operation, maintenance and spare-part manuals of the goods (Equipment).

Items offered should be covered by at least 3 Years warranty (if applicable) from the date of delivery to the Purchaser/Procuring Entity. Goods offered shall be new, unused and based on the manufacturer's current and most recent model

### **2) Recipient of Goods:**

The Recipient of Goods is:

**Meghalaya Basin Development Authority (MBDA)**

**Procurement Division**

**RDL Building, 3rd Floor, Springside Opposite HP Office**

**Lumsohphoh, Nongthymmai – 793014**

**Email: [kfwmbdaprocurement@gmail.com](mailto:kfwmbdaprocurement@gmail.com)**

### **3) Delivery and Installation**

All equipment shall be forwarded to the destination as per No. 2 under the responsibility of the Supplier within 30 days after signing of the contract. The supplier is responsible for the installation and instruction of the end-users pursuant to the instruction procedures of the manufacturers. The manuals must be delivered in English and for selected items in English language as indicated in the schedule of requirements.

### **4) Post-Sales Service:**

Please provide details of any after-sales service that you offer, including technical support and maintenance

### Section VIII: Price Schedule of Goods

<b>Currencies in accordance with Section III No. 13</b>						Date: [Insert]	
						RFQ. No.: [Insert]	
						Page [Inserts] of [Insert]	
1	2	3	4	5	6	7	8
Line Item No.	Description of Goods*	Country of Origin	Delivery Time in Days at named place of CIP destination [Insert final destination(s) in the Purchaser's country]	Quantity and Physical unit (Nos.)	CIP Unit Price & Currency excluding Custom Duties and Import Taxes paid, in accordance with Section I No. 14	Sales and other taxes paid or payable if Contract is awarded.	Currency & Total Price per line item (Col. 5 x 6)
Lot#							
<b>Total Price (including currency) CIP plus local services (if any) [Insert name of Purchaser's Country]</b>							

Name of Bidder:

Signature of Bidder

Date:

\*Description of goods to be provided along with the warranty

## Section IX: Schedule of Technical Specifications of Goods

Lot #	Item	Nos	Specifications
Lot 1	Camera Body 1	2	<p><b>Image Sensor and Processor</b>          Sensor: 61.0 MP back-illuminated full-frame CMOS sensor.          Processor: High-speed image processing engine paired with a dedicated AI-driven computing unit for advanced subject recognition and tracking.</p> <p><b>Image Stabilization</b>: 5-axis in-body sensor-shift stabilization with up to approximately 8 stops of compensation.</p> <p><b>Autofocus</b>          AF System: Next-generation, AI-enhanced real-time autofocus system utilizing deep-learning algorithms.          Subject Detection: Intelligent recognition and tracking for humans (including pose estimation), animals, birds, insects, as well as vehicles such as cars, trains, and airplanes.          Focus Points: 693 phase-detection points covering a large portion of the image area.</p> <p><b>Video Recording</b>          Maximum Resolution: 8K recording at 24p/25p with full pixel readout.          Additional Formats: UHD 4K recording up to 60p/50p (with approx. 1.2x crop) and Full HD up to 120 fps for smooth slow-motion capture.</p> <p><b>Color Depth and Output</b>: Supports internal 10-bit 4:2:2 recording and 16-bit RAW output via HDMI. Includes advanced logarithmic and cinema-style picture profiles for flexible color grading workflows.</p> <p><b>Audio</b>: Built-in stereo recording plus 3.5 mm microphone input and headphone monitoring ports.</p> <p><b>Photography</b>          Continuous Shooting: Up to 10 fps with full AF/AE tracking.          RAW Formats: Multiple RAW size options (lossless compressed in several resolutions, plus uncompressed), all with 14-bit depth.          ISO Range: Native sensitivity from ISO 100–32,000, expandable to ISO 50–102,400.</p> <p><b>Body, Display, and Connectivity</b>          Viewfinder: 9.44-million-dot QXGA OLED electronic viewfinder with 0.90x magnification and a 120 fps refresh rate mode.          LCD Monitor: 3.2-inch, 4-axis multi-angle touchscreen with 2.1-million-dot resolution, combining the advantages of tilt and vari-angle mechanisms.          Durability: Weather-sealed magnesium-alloy construction with sensor anti-dust technology.          Memory Slots: Dual card slots compatible with CFexpress Type A and SD (UHS-II) media.          Ports &amp; Wireless: Features a high-speed USB-C interface, full-size HDMI port, and integrated Wi-Fi and Bluetooth connectivity.</p>

Camera Body 2	<p><b>Image Sensor and Processor</b>      Sensor: 12.1-megapixel full-frame (35.6 × 23.8 mm) back-illuminated CMOS sensor.      Image Processor: High-performance processing engine delivering up to roughly 8× faster throughput compared to earlier generations.</p> <p><b>ISO Sensitivity</b>      Still Images: ISO 80–102400 (expandable to ISO 40–409600).      Video: ISO 80–102400 (expandable up to ISO 409600).</p> <p><b>Autofocus</b>      AF System: Advanced hybrid autofocus system combining phase-detection and contrast-detection methods.      Focus Points: 759 phase-detection points covering a wide imaging area.      Subject Tracking: Real-time eye-detection autofocus for both stills and video.</p> <p><b>Image Stabilization</b>      Type: 5-axis sensor-shift in-body image stabilization.      Effectiveness: Rated for up to approximately 5.5 stops of compensation.</p> <p><b>Continuous Shooting</b>      Burst Rate: Up to 10 frames per second with continuous autofocus and auto-exposure.</p> <p><b>Storage Media</b>      Memory Slots: Dual card slots supporting both CFexpress Type A and SD (UHS-II) cards.</p> <p><b>Body and Design</b>      Construction: Robust magnesium-alloy chassis with comprehensive weather-sealing against dust and moisture.      Viewfinder: 9.44-million-dot QXGA OLED electronic viewfinder with 0.9× magnification.      LCD Monitor: 3.0-inch, 1.44-million-dot fully articulated side-opening vari-angle touchscreen.</p> <p><b>Video Features</b>  <p><b>Internal Recording</b>      Resolution &amp; Frame Rates: UHD 4K (3840 × 2160) at up to 120p.      Color Depth &amp; Sampling: 10-bit 4:2:2 internal recording available in all modes.      Codecs: Supports advanced HEVC/H.265-based compression options and high-bit-rate All-Intra recording modes for consistent quality.      Gamma &amp; Profiles: Includes logarithmic and HDR-oriented picture profiles offering more than 15 stops of dynamic range for grading flexibility.      Recording Limits: No fixed maximum clip length; designed with enhanced thermal management for extended recording durations.</p> <p><b>External Output</b>      RAW Output: Capable of transmitting 16-bit RAW video to an external recorder via a full-size HDMI Type-A port.</p> <p><b>Slow &amp; Quick Motion</b>      High-Speed Options: Supports frame rates up to 240 fps in Full HD for smooth slow-motion effects.</p> <p><b>Audio</b></p> </p>
---------------	--

Digital Interface: Features a digital audio interface through the accessory shoe, enabling high-quality multichannel audio (up to 4-channel, 24-bit) when used with an appropriate audio adapter.  
Inputs/Outputs: Support for external audio accessories for improved sound capture.

Camera Bag type 1	1	<p>Carry/Transport Options      Backpack Straps, Belt Loop, Handle</p> <p>Color      Black</p> <p>Type of Closure      Main Compartment: Zipper</p> <p>Laptop/Tablet Compartment      Single Compartment: Fits 13" Laptop</p> <p>Interior Type      Main Compartment: Insert with Adjustable Dividers (Hook &amp; Loop)</p> <p>Secondary Compartment: Tech Panels</p> <p>Monopod/Tripod Holder      Yes</p> <p>Security Lock      None</p> <p>Features      Bottle Pocket</p> <p>Environmental</p> <p>IP Rating      None</p> <p>General</p> <p>Materials      Exterior: Polyester</p> <p>Insulation: Foam, Polyurethane</p> <p>Padded Interior      Yes</p> <p>Dimensions      Exterior 18.1 x 12.4 x 7.9" / 46 x 31.5 x 20.1 cm</p> <p>Interior 14.6 x 9.4 x 5.1" / 37.1 x 23.9 x 13 cm</p> <p>Accessory Pocket 14.6 x 9.4 x 5.1" / 37.1 x 23.9 x 13 cm (Camera Compartment) 9.8 x 6.7 x 0.8" / 24.9 x 17 x 2 cm (Front Compartment)</p> <p>Weight      6.58 lb / 2.98 kg</p>
----------------------	---	---

Camera Bag type 2	2	<p>Carry/Transport Options      Backpack Straps with Sternum Strap, Handle, Waist Belt</p> <p>Color      Black</p> <p>Type of Closure      Zipper</p> <p>Laptop/Tablet Compartment      Single Compartment: Fits 15" Laptop</p> <p>Interior Type      Adjustable Dividers (Hook &amp; Loop)</p> <p>Monopod/Tripod Holder      Yes</p> <p>Environmental</p> <p>Water Resistance      Rain Cover, Water Resistant (Material)</p> <p>General</p> <p>Materials      Exterior: Nylon</p> <p>Dimensions      Exterior 18.9 x 13 x 9.4" / 48.01 x 33.02 x 23.88 cm</p> <p>Interior 16.1 x 11 x 5.5" / 40.89 x 27.94 x 13.97 cm</p> <p>Weight      3.7 lb / 1.7 kg</p> <p>Packaging Info</p> <p>Package Weight      4 lb</p> <p>Box Dimensions (LxWxH)      16 x 11 x 8"</p>
----------------------	---	--

360 action cam with accessories	<p>8K 360° Action Camera — Full Technical Specifications</p> <p>Core Imaging Hardware</p> <p>Sensor Size: 1/1.28"</p> <p>Lens Aperture: f/2.0</p> <p>Focal Length: 6 mm</p> <p>360° Video Resolution</p> <p>Video Mode:</p> <ul style="list-style-type: none"> <li>8K: 7680×3840 @ 30/25/24 fps</li> <li>5.7K+: 5760×2880 @ 30/25/24 fps</li> <li>5.7K: 5760×2880 @ 60/50/48/30/25/24 fps</li> <li>4K: 3840×1920 @ 120/100/60/50/48/30/25/24 fps</li> </ul> <p>Frame-Based Mode:</p> <ul style="list-style-type: none"> <li>5.7K+: 30/25/24 fps</li> <li>5.7K: 30/25/24 fps</li> <li>1080p: 30/25/24 fps</li> </ul> <p>Low-Light Enhanced Mode:</p> <ul style="list-style-type: none"> <li>8K: 30/25/24 fps</li> <li>5.7K: 30/25/24 fps</li> <li>4K: 30/25/24 fps</li> </ul> <p>Single-Lens Video Resolution</p> <p>Video Mode:</p> <ul style="list-style-type: none"> <li>4K: 3840×2160 @ 60/50/30/25/24 fps</li> <li>2.7K: 2720×1536 @ 60/50/30/25/24 fps</li> <li>1080p: 1920×1080 @ 120/100/60/50/30/25/24 fps</li> </ul> <p>Square Video Modes (FreeFrame):</p> <ul style="list-style-type: none"> <li>4K (1:1): 3840×3840 @ 30/25/24 fps</li> <li>2.7K (1:1): 2720×2720 @ 60/50/30/25/24 fps</li> <li>1080p (1:1): 1920×1920 @ 60/50/30/25/24 fps</li> </ul> <p>Tracking/Self-Capture Modes:</p> <ul style="list-style-type: none"> <li>4K: 30/25/24 fps</li> <li>2.7K: 120/100/60/50/30/25/24 fps</li> <li>1080p: 120/100/60/50/30/25/24 fps</li> </ul> <p>Photo Resolution</p> <ul style="list-style-type: none"> <li>Approx. 72 MP: 11904×5952</li> <li>Approx. 18 MP: 5888×2944</li> </ul> <p>Formats</p> <p>Video: INSV (360°), MP4 (single-lens)</p>
---------------------------------	--

Photo: INSP, DNG  
Video Modes:  
360°: HDR, low-light enhanced mode, frame-based, timelapse, speed-ramp mode, bullet-time capture, loop recording, road capture  
Single-Lens: Standard video, square-format, tracking/self mode, loop recording  
Photo Modes:  
Standard photo, HDR photo, interval, star-lapse, burst  
Color & Encoding  
Color Profiles: Vivid, Standard, Flat  
Log Profile: Supported  
Codecs: H.264, H.265  
Max Video Bitrate: 180 Mbps  
Exposure & Imaging Controls  
Exposure Compensation: ±4 EV  
ISO Range: 100–6400  
Shutter Speed:  
Photo: 1/8000 – 120 s  
Video: 1/8000 – frame-limit  
White Balance: 2000K – 10000K  
Audio System  
Audio Modes: Auto wind reduction, voice enhancement, stereo, 360° audio  
Audio Format: 48 kHz, 16-bit, AAC  
Microphones: 4  
Storage & I/O  
Memory Card: UHS-I V30 or higher  
USB Port: USB-C 3.0  
Battery & Power  
Battery Capacity: 2400 mAh  
Charging Time:  
80% in ~20 min (9V 2A)  
100% in ~35 min (9V 2A)  
Run Time:  
8K 30 fps: ~88 min  
5.7K 30 fps: ~135 min  
5.7K 24 fps (endurance mode): ~185 min  
Physical Specifications  
Weight: 200 g

Dimensions: 46 × 124.5 × 38.2 mm  
Operating Temperature: -4°F to 104°F (-20°C to 40°C)  
Water Resistance: 15 m rating  
Mounting Point: 1/4"  
Quick Release: Yes  
Color: Black  
Connectivity  
Bluetooth: BLE 5.2  
Wi-Fi: 802.11 a/n/ac  
Gyroscope: 6-axis  
Included Accessories:  
8K 360° Action Camera  
3.7 ft telescoping selfie stick  
Standard lens guards ×2  
2400 mAh batteries ×2  
Lens cap  
Fast-charge storage/charging case  
USB-C charging cable  
Carrying case  
Protective pouch  
Lens cleaning cloth

Handheld action camera with accessories	1	<p>1-Inch Sensor Compact Gimbal Camera — Full Specifications</p> <p>Core Imaging Specs</p> <p>Sensor: 1-inch CMOS</p> <p>Video Resolution: Up to 4K at 120 fps</p> <p>Color Profiles: Must Log and 10-bit color depth for professional grading</p> <p>Focus System: Full-pixel fast focusing</p> <p>Tracking: Advanced subject tracking for face and object detection</p> <p>Photo &amp; Video Stabilization: 3-axis mechanical gimbal stabilization</p> <p>Screen: 2-inch rotatable touchscreen with automatic horizontal/vertical orientation</p> <p>Audio</p> <p>Microphones: Built-in stereo microphones for enhanced audio capture</p> <p>Storage</p> <p>Media: Requires a microSD card (not included)</p> <p>Creator Combo Add-Ons</p> <p>Wireless Audio Transmitter</p> <p>High-quality clip-on wireless audio solution included for clean, remote sound capture.</p> <p>Wide-Angle Lens</p> <p>Expands the camera's field of view for immersive shots.</p> <p>Battery Handle</p> <p>Extends runtime significantly when attached.</p> <p>Mini Tripod</p> <p>Allows stable placement on flat surfaces or tabletop shooting.</p> <p>Handle with 1/4" Thread</p> <p>Enables mounting to external rigs, tripods, or accessories.</p> <p>Other Included Accessories</p> <p>Protective cover</p> <p>Wrist strap</p> <p>Carrying bag</p>
---	---	--

Lot #	Item	Nos	Specification
Lot 2	Camera Battery	12	<p>Dimensions (W × H × D): Approx. 38.7 x 22.7 x 51.7 mm (1.56 x 0.91 x 2.13)            Weight: Approx. 83 g (3.0 oz)            Capacity: 7.2 V/16.4 Wh (2,280 mAh)</p>
	Battery Grip	4	<p>Dimensions (W × H × D): Approx. 128.8 x 108.9 x 67 mm (5 1/8 x 4 3/8 x 2 3/4)            Weight: Approx. 290 g (10.2 oz)            Battery type: NP-FZ100</p>

Rechargeable AA battery (pack of 4) with charger	<p>1</p> <p><b>Rechargeable AA Ni-MH Battery &amp; Charger</b></p> <p><b>Battery Specifications</b></p> <p>Battery type: AA, Nickel-Metal Hydride (Ni-MH).</p> <p>Capacity: Up to 2550 mAh, with a minimum guaranteed capacity of 2450 mAh.</p> <p>Voltage: 1.2V.</p> <p>Cycle life: Rechargeable up to 500 cycles.</p> <p>Low self-discharge: Retains about 85% charge after one year of storage, making it suitable for long-term standby use.</p> <p>Ready-to-use: Delivered pre-charged from the factory.</p> <p>No memory effect: Can be recharged whether partially or fully drained without impacting overall capacity.</p> <p>Temperature performance: Operates from -20°C to 50°C (-4°F to 122°F), though performance decreases in extreme conditions.</p> <p>Ideal for: High-drain electronics such as external camera flashes, digital cameras, RC devices, and various wireless electronics.</p> <p><b>Charger Specifications</b></p> <p><b>Charging Capabilities</b></p> <p>Battery compatibility: Charges 1–4 Ni-MH batteries in any mix of AA or AAA sizes.</p> <p>Individual charging: Uses independent charge-control technology, allowing each battery to be monitored and charged separately.</p> <p>Approximate charging times: (Times vary by battery capacity and number of batteries inserted)</p> <p>Standard AA (1900–2000 mAh):</p> <ul style="list-style-type: none"> <li>1–2 batteries: 1.5 hours</li> <li>3–4 batteries: 3 hours</li> </ul> <p>High-capacity AA (2450–2550 mAh):</p> <ul style="list-style-type: none"> <li>1–2 batteries: 2 hours</li> <li>3–4 batteries: 4 hours</li> </ul> <p>AAA (750–800 mAh):</p> <ul style="list-style-type: none"> <li>1–2 batteries: 1.5 hours</li> <li>3–4 batteries: 3 hours</li> </ul> <p><b>Safety and Features</b></p> <p>Smart charge control: Automatically detects voltage and stops charging before overcharging occurs, helping extend battery lifespan.</p> <p>LED indicators: Four individual 3-color LEDs display charging progress for each battery slot:</p> <ul style="list-style-type: none"> <li>Red: Less than 20% charged</li> </ul>
--	--

	<p>Yellow: 20–80% charged Green: 80–99% charged Light off: Fully charged Error detection: Flashing yellow: Battery near end of life Flashing red: Invalid or non-rechargeable battery detected; charging is disabled for that slot Universal voltage: Supports AC 100–240V, suitable for worldwide use. Integrated plug: Built-in, retractable AC plug for direct wall-outlet charging without cables. Physical Specifications Dimensions: 68 × 120 × 28 mm Weight: Approx. 120 g</p>
--	---

Powerbank	4	<p><b>High-Capacity 27,650mAh / 99.54Wh Power Bank</b></p> <p><b>Core Specifications</b></p> <p>Capacity: 27,650mAh (99.54Wh)</p> <p>Dimensions: 57 × 49.7 × 161.7 mm (approx. 6.37 × 2.24 × 1.96 inches)</p> <p>Weight: 665 g (approx. 1.47 lbs)</p> <p><b>Ports &amp; Output</b></p> <p>USB-C Ports: 2 × USB-C (up to 140W each)</p> <p>USB-A Port: 1 × USB-A (up to 65W)</p> <p>Total Maximum Output: 250W</p> <p>Charging Standard: Power Delivery 3.1</p> <p><b>Key Features &amp; Performance</b></p> <p><b>Ultra-Fast Device Charging</b></p> <p>Can charge a 16-inch laptop (e.g., models with high-power 140W USB-C input) from 0–50% in around 28 minutes.</p> <p><b>High-Speed Recharging</b></p> <p>Fully recharges in approximately 37–43 minutes when using both USB-C ports simultaneously for up to 170W combined input.</p> <p><b>Airline-Friendly</b></p> <p>The 99.54Wh capacity is within standard international airline limits for carry-on battery packs.</p> <p><b>App Connectivity</b></p> <p>Supports Bluetooth connection to a mobile app for:</p> <ul style="list-style-type: none"> <li>Real-time charging stats</li> <li>Sound-based location alerts</li> <li>Optimization of charging performance</li> </ul> <p><b>Smart Digital Display</b></p> <p>Built-in screen shows:</p> <ul style="list-style-type: none"> <li>Battery percentage</li> <li>Individual port activity</li> <li>Charging and discharging status</li> </ul> <p><b>Broad Compatibility</b></p> <p>Works with a wide range of devices, including:</p> <ul style="list-style-type: none"> <li>Laptops</li> <li>Smartphones</li> <li>Tablets</li> <li>Handheld gaming devices (e.g., Steam Deck)</li> <li>Compact camera drones and other USB-C powered gear</li> </ul>
-----------	---	--

	<p><b>Advanced Safety System</b> Includes upgraded internal protection features for stable temperature control, power management, and safe fast charging.</p> <p><b>Optional Charging Base</b> Compatible with a 100W drop-and-go desktop charging base (sold separately) for hands-free, high-speed recharging.</p>
--	--

Lot #	Item	Nos	Specification
Lot 3	960 TB CFexpress 4.0 Type A Memory Card	4	<p>Capacity: 960 GB</p> <p>Interface: PCI Express Gen4 x1</p> <p>Maximum Read Speed: Up to 1800 MB/s</p> <p>Maximum Write Speed: Up to 1700 MB/s</p> <p>Video Performance Guarantee: VPG400 certification for sustained, stable video capture</p> <p>Dimensions (W × H × D): 20.0 mm × 28.0 mm × 2.8 mm</p> <p>Operating Temperature: -12°C to +72°C (10.4°F to 161.6°F), non-condensing</p> <p><b>Key Features</b></p> <p>Reinforced Construction: Engineered with a rugged, high-strength design capable of enduring harsh environmental conditions such as extreme temperatures, X-rays, electrostatic discharge, and strong UV exposure.</p> <p>Enhanced Durability: Offers exceptional resistance to drops and bending, far exceeding the baseline requirements for CFexpress Type A media.</p> <p>IP57 Rating: Provides robust protection against dust ingress and temporary water exposure to safeguard stored data.</p> <p>Reliable Video Capture: VPG400 certification ensures consistent, uninterrupted recording for high-resolution and high-bitrate video workflows.</p> <p>High-Speed Workflow: Delivers fast data transfer performance and supports the CFexpress 4.0 specification when used with compatible devices, enabling efficient file offloading and production workflows.</p>

480 TB CFexpress 4.0 Type A Memory Card	4	<p><b>Key Specifications</b></p> <p>Card Type: CFexpress Type A Storage Capacity: 480 GB Bus Type: PCI Express 4.0 Read Speed (Sustained): Up to 1800 MB/s Write Speed: Maximum: Up to 1700 MB/s Sustained: 800 MB/s Minimum: 200 MB/s Video Performance Guarantee: VPG200 certification for stable, continuous video capture</p> <p><b>Environmental Specifications</b></p> <p>Operating Temperature: -12°C to 72°C (10°F to 161°F) Storage Temperature: -20°C to 85°C (-4°F to 185°F)</p> <p><b>Packaging Information</b></p> <p>Package Weight: Approximately 0.02 lb Box Dimensions (L × W × H): 2.1 × 1.7 × 0.4 inches</p>
--	---	---

<p>512GB UHS-II microSDXC Memory Card with SD Adapter</p>	<p>7</p>	<p>Card Type microSDXC with Full-Size SD Adapter Storage Capacity 512 GB Bus Type UHS-II Speed Class 10 UHS Speed Class U3 Video Speed Class V60 Read Speed Maximum: 250 MB/s Write Speed Maximum: 130 MB/s Minimum: 60 MB/s Built-in Write-Protect Switch On Adapter Only Operating Conditions -13 to 185°F / -25 to 85°C Storage Conditions -40 to 185°F / -40 to 85°C Packaging Info Package Weight 0.02 lb Box Dimensions (LxWxH) 2.1 x 1.7 x 0.45"</p>
---	----------	---

CFexpress® Type A Reader	2	<p>Dual-Slot Memory Card Reader</p> <p>Supported Media Cards</p> <p>CFexpress Type A</p> <p>SD, SDHC, SDXC (supports both UHS-I and UHS-II)</p> <p>Interface &amp; Transfer Performance</p> <p>Interface: USB 3.2 Gen 2 (also known as USB 3.1 Gen 2)</p> <p>Maximum data transfer rate: Up to 10 Gbps</p> <p>(Actual speed depends on card type and host system.)</p> <p>Design &amp; Connectivity</p> <p>Host connection: USB Type-C</p> <p>Included cables:</p> <p>USB-C to USB-C</p> <p>USB-C to USB-A</p> <p>Power source: USB bus-powered (no external adapter required)</p> <p>Status indicator: LED shows card detection and flashes during data activity</p> <p>Form factor: Slim, lightweight, and pocket-friendly</p> <p>Recessed slot: Helps prevent accidental card ejection</p> <p>Physical Specifications</p> <p>Dimensions:</p> <p>55 × 12 × 95 mm (2.17 × 0.47 × 3.74 inches)</p> <p>Weight: 95 g (3.4 oz)</p> <p>Operating Environment</p> <p>Temperature range: 5°C to 40°C (41°F to 104°F), non-condensing</p>
--------------------------	---	--

SSD External hard drive 4TB	2	Interface    USB 3.2 Gen-2 2x2 (20Gb/s) Form factor - External Portable Capacity - 4TB Speed & timing: Sequential Read - 2100 Sequential Write - 2000
--------------------------------	---	--

Lot #	Item	Nos	Specification
Lot 4	Zoom Lens - 24–70 mm F2.8 GM II	4	<p>Key Specifications</p> <p>Lens Mount: Must be compatible with the camera bodies</p> <p>Format Coverage: 35mm full-frame.</p> <p>Focal Length: 24–70mm zoom range.</p> <p>Maximum Aperture: f/2.8</p> <p>Minimum Aperture: f/22</p> <p>Aperture Blades: 11-blade rounded diaphragm for smooth, natural bokeh.</p> <p>Optical Construction</p> <p>Optical Design: 20 elements in 15 groups.</p> <p>Special Elements: Includes multiple aspherical elements (including high-precision, large-diameter types), as well as ED and Super ED glass elements to minimize aberrations and maintain edge-to-edge sharpness.</p> <p>Lens Coating: Advanced anti-reflective coating applied to reduce flare, ghosting, and maintain high contrast in strong lighting.</p> <p>Autofocus System</p> <p>AF Drive: Utilizes multiple high-speed linear motors for fast, accurate, and quiet autofocus performance suitable for both stills and video.</p> <p>Close Focusing</p> <p>Minimum Focus Distance:</p> <p>At 24mm: 8.3 in (0.21 m)</p> <p>At 70mm: 11.8 in (0.30 m)</p> <p>Maximum Magnification: 0.32× at 70mm</p> <p>Physical Characteristics</p> <p>Filter Diameter: 82 mm</p> <p>Dimensions (Diameter × Length): 87.8 × 119.9 mm (3.46 × 4.72 in)</p>

Weight: 695 g (1.5 lb), offering a compact and lightweight build for a constant-aperture zoom.

**Durability**

Weather Sealing: Dust- and moisture-resistant construction designed for outdoor use.

Front Element Protection: Fluorine coating to resist fingerprints, oil, water, and smudges.

Prime Lens - 85mm f/1.2	2	<p><b>Key Specifications</b></p> <p><b>Mount &amp; Format</b></p> <p>Lens Mount: Must be compatible with the camera bodies</p> <p>Format Coverage: 35mm full-frame</p> <p>APS-C Equivalent Focal Length: 127.5mm (when used on APS-C bodies)</p> <p><b>Optics</b></p> <p>Focal Length: 85mm</p> <p>Optical Construction: 11 groups with 14 total elements</p> <p>Angle of View (Full-Frame): 29°</p> <p>Angle of View (APS-C): Approximately 19°</p> <p><b>Aperture</b></p> <p>Maximum Aperture: f/1.4</p> <p>Minimum Aperture: f/16</p> <p>Aperture Blades: 11</p> <p>Rounded Diaphragm: Yes, for smooth background blur (bokeh)</p> <p><b>Focusing</b></p> <p>Minimum Focus Distance:</p> <p>Autofocus: 0.85 m (2.79 ft)</p> <p>Manual Focus: 0.80 m (2.63 ft)</p> <p>Maximum Magnification:</p> <p>AF: 0.11×</p> <p>MF: 0.12×</p> <p><b>Image Stabilization</b></p> <p>Optical Stabilization: Not included (designed for use with bodies featuring in-body stabilization)</p> <p><b>Teleconverter Compatibility</b></p> <p>1.4× Teleconverter: Not supported</p> <p>2.0× Teleconverter: Not supported</p> <p><b>Physical Characteristics</b></p> <p>Filter Diameter: 77 mm</p> <p>Dimensions (Diameter × Length): 84.7 × 107.3 mm (3.38 × 4.25 in)</p> <p>Weight: 642 g (22.7 oz)</p> <p><b>Included Accessories (Genericized)</b></p> <p>Lens Hood: Round, bayonet-mount hood</p> <p>Front Cap: Standard 77 mm front lens cap</p> <p>Rear Cap: Standard mirrorless-mount rear cap</p> <p>Carrying Case: Soft protective pouch</p>
-------------------------	---	---

Macro : 90 mm F2.8 Macro G OSS	1	<p><b>Key Specifications</b></p> <p><b>Optical Features</b></p> <p><b>Focal Length:</b> 90mm</p> <p><b>Maximum Magnification:</b> 1.0× (true 1:1 macro reproduction)</p> <p><b>Optical Construction:</b> 15 elements in 11 groups</p> <p><b>Special Elements:</b> Incorporates one aspherical element and multiple extra-low-dispersion elements—including a high-performance variant—to minimize chromatic and spherical aberrations</p> <p><b>Lens Coating:</b> Advanced anti-reflective coating applied to reduce flare and ghosting</p> <p><b>Aperture:</b> 9-blade rounded diaphragm for smooth, attractive bokeh</p> <p><b>Floating Focus Mechanism:</b> Ensures consistent sharpness and optical performance throughout the entire focusing range</p> <p><b>Focus and Stabilization</b></p> <p><b>Focus System:</b> Internal focusing driven by a quiet, high-precision dual linear motor system</p> <p><b>Minimum Focus Distance:</b> 0.28 m (0.92 ft)</p> <p><b>Image Stabilization:</b> Integrated optical stabilization system designed to improve handheld shooting clarity</p> <p><b>Focus Controls:</b></p> <p>Focus ring can be slipped between manual and autofocus modes</p> <p>Dedicated focus-hold button on the lens barrel</p> <p>Focus-range limiter switch for optimized autofocus speed in restricted focus ranges</p> <p><b>Physical and Design Characteristics</b></p> <p><b>Lens Mount:</b> Must be compatible with the camera bodies</p> <p><b>Format Coverage:</b> 35mm full-frame</p> <p><b>Filter Diameter:</b> 62 mm</p> <p><b>Dimensions (Diameter × Length):</b> 79 × 130.5 mm</p> <p><b>Weight:</b> 602 g (21.3 oz)</p> <p><b>Build Quality:</b> Weather-resistant construction designed to withstand dust and moisture in demanding shooting environments</p>
-----------------------------------	---	---

Wide angle Lens - FE 12–24 mm F2.8 GM	2	<p><b>Key Specifications</b></p> <p><b>Mount &amp; Format</b></p> <p>Lens Mount: Must be compatible with the camera bodies</p> <p>Format Coverage: Full-frame (35mm)</p> <p><b>Optics</b></p> <p>Focal Length: 12–24 mm ultra-wide zoom</p> <p>Aperture Range: f/2.8 to f/22</p> <p>Optical Construction: 17 elements arranged in 14 groups</p> <p>Filter Type: Rear-mounted gel filter holder</p> <p>Minimum Focus Distance: 0.28 m</p> <p>Diagonal Angle of View: 122°–84°</p> <p>Diaphragm: 9-blade rounded aperture for smooth, natural bokeh</p> <p><b>Key Features &amp; Technologies (Genericized)</b></p> <p>Autofocus System: Driven by multiple high-speed linear motors for fast, accurate, and quiet focusing, suitable for both stills and video</p> <p>Specialized Elements:</p> <p>Multiple high-precision aspherical elements to maintain edge-to-edge sharpness</p> <p>Extra-low-dispersion and advanced dispersion-control glass elements to suppress chromatic aberration</p> <p>Lens Coating: Advanced anti-reflective coating reduces flare and ghosting while improving contrast in challenging light</p> <p>Floating Focus Design: Maintains high image quality across the entire zoom range and at all focusing distances</p> <p>Weather-Resistant Build: Sealed against dust and moisture for reliable performance in harsh environments</p> <p>Integral Lens Hood: Built-in petal-style hood helps reduce stray light and offers physical protection for the front element</p> <p>Rear Filter Holder: Supports standard sheet-type filters for enhanced creative control</p>
--	---	--

<p>Telephoto Lens - Super telephoto Zoom 100-400mm G Master lens</p>	<p><b>Key Specifications</b></p> <p><b>Optical</b></p> <p>Focal Length: 100–400 mm telephoto zoom</p> <p>Aperture Range: f/4.5–f/5.6 (wide) to f/32–f/40 (narrow)</p> <p>Optical Construction: 22 elements in 16 groups</p> <p>Special Elements: Incorporates multiple extra-low dispersion elements, including a high-grade variant, to reduce chromatic aberration</p> <p>Aperture Diaphragm: 9-blade rounded aperture for smooth, natural bokeh</p> <p>Maximum Magnification: 0.35×</p> <p>Minimum Focus Distance: 0.98 m (3.22 ft)</p> <p><b>Autofocus and Stabilization</b></p> <p>Autofocus Drive: Combination of a precision ultrasonic motor and dual linear motors for fast, quiet, and accurate focusing</p> <p>Image Stabilization: Integrated optical stabilization system designed to support sharp handheld shooting</p> <p><b>Focus Features:</b></p> <p>Internal focusing mechanism</p> <p>Focus range limiter switch</p> <p>Customizable focus-hold buttons on the barrel</p> <p><b>Physical and Build Quality</b></p> <p>Weight: 1395 g (49.3 oz) without tripod mount</p> <p>Dimensions: 93.9 mm (diameter) × 205 mm (length)</p> <p>Filter Diameter: 77 mm</p> <p>Construction: Weather-resistant build featuring dust- and moisture-resistant materials, including magnesium alloy components</p> <p><b>Lens Coatings:</b></p> <p>Advanced anti-reflective coating to reduce flare and ghosting</p> <p>Fluorine coating on the front element to repel moisture, oils, and dirt</p> <p><b>Tripod Collar:</b> Removable, rotating tripod mount included</p> <p><b>Zoom Torque Adjustment:</b> Adjustable zoom tension ring enables control over zoom resistance</p> <p><b>Compatibility</b></p> <p><b>Lens Mount:</b> Must be compatible with the camera bodies</p> <p><b>Teleconverter Support:</b> Compatible with optional 1.4× and 2.0× teleconverters for</p>
1	

extended reach (when supported by the camera system)  
APS-C Equivalent Focal Length: Approximately 150–600 mm when used on an  
APS-C format body

<p>Telephoto Lens - 50–150 mm F2 GM</p> <p>1</p>	<p><b>Key Specifications</b></p> <p><b>Mount &amp; Optics</b></p> <p>Lens Mount: Must be compatible with the camera bodies</p> <p>Focal Length: 50–150 mm</p> <p>Aperture Range:</p> <p>Maximum: f/2</p> <p>Minimum: f/22</p> <p>Optical Construction: 19 elements arranged in 17 groups</p> <p>Special Optical Elements: Includes multiple high-precision aspherical elements and several extra-low-dispersion glass elements (including advanced low-dispersion types) to reduce aberrations and enhance clarity</p> <p><b>Aperture &amp; Focus</b></p> <p>Diaphragm Blades: 11-blade rounded aperture for smooth bokeh</p> <p>Autofocus Drive: Quad linear-motor focusing system providing fast, accurate, and quiet AF performance</p> <p>Minimum Focus Distance:</p> <p>50 mm: 0.4 m (1.32 ft)</p> <p>150 mm: 0.74 m (2.43 ft)</p> <p>Maximum Magnification: 0.20×</p> <p>Autofocus: Supported</p> <p>Image Stabilization: Not included (designed for use with camera bodies that offer in-body stabilization)</p> <p><b>Physical Characteristics</b></p> <p>Filter Diameter: 95 mm</p> <p>Dimensions (Diameter × Length): 102.8 × 200 mm (4-1/8 × 7-7/8 in)</p> <p>Weight: 1,340 g (47.3 oz), excluding tripod mount</p> <p>Weather Sealing: Dust- and moisture-resistant design</p> <p>Lens Coatings: Advanced anti-reflective coating to reduce flare and ghosting, plus a fluorine-coated front element for easier cleaning and resistance to dirt, oil, and moisture</p>
--	--

<p>Telephoto Lens - 70-200mm f/2.8 VR S LENS</p>	<p>1</p> <p>Technical Specifications</p> <p>Mount &amp; Imaging Format</p> <p>Lens Mount: Must be compatible with the camera bodies</p> <p>Format Coverage: 35mm full-frame</p> <p>Optics &amp; Focal Range</p> <p>Focal Length: 70–200 mm</p> <p>Aperture Range:</p> <p>Maximum: f/2.8</p> <p>Minimum: f/22</p> <p>Aperture Blades: 11-blade rounded diaphragm for smooth background blur</p> <p>Optical Construction: 17 elements in 14 groups</p> <p>Close-Focus &amp; Magnification</p> <p>Minimum Focus Distance:</p> <p>70 mm: 0.4 m (1.32 ft)</p> <p>200 mm: 0.82 m (2.69 ft)</p> <p>Physical Characteristics</p> <p>Weight: 1,045 g (2.3 lb)</p> <p>Dimensions (Diameter × Length): 88 × 200 mm (3.5 × 7.88 in)</p> <p>Filter Diameter: 77 mm</p> <p>Weather Resistance: Dust- and moisture-resistant construction</p> <p>Front Element Protection: Fluorine-coated front element to resist oil, dirt, and moisture</p> <p>Advanced Features (Generic Terminology)</p> <p>Autofocus System</p> <p>Utilizes a quad linear-motor focusing system that provides high-speed, high-precision, and low-noise autofocus performance.</p> <p>Offers improved subject-tracking performance compared with earlier-generation designs.</p> <p>Image Stabilization</p> <p>Equipped with built-in optical image stabilization, including:</p> <p>Standard stabilization mode</p> <p>Panning mode</p> <p>Enhanced stabilization mode for irregular camera movement</p> <p>Aberration Control</p> <p>Includes a combination of advanced optical elements that suppress chromatic, spherical, and distortion-related aberrations:</p> <p>One high-precision aspherical element</p> <p>Two additional aspherical elements</p> <p>Two extra-low-dispersion elements of higher specification</p>
--	---

			<p>Two standard extra-low-dispersion elements</p> <p>Anti-Reflective Coatings</p> <p>Advanced multi-layer anti-reflection coating to suppress flare, ghosting, and internal reflections.</p> <p>Video-Optimized Design</p> <p>Optical and mechanical design minimizes:</p> <p>Focus breathing</p> <p>Focus shift during zoom</p> <p>Axis shift when adjusting focal length</p> <p>External Controls</p> <p>Dedicated rings for manual focus, zoom, and aperture</p> <p>De-clickable aperture option for smooth exposure changes during video recording</p> <p>Teleconverter Compatibility</p> <p>Compatible with 1.4× and 2× teleconverters, enabling extended reach while retaining autofocus functionality (depending on host camera capability).</p>
--	--	--	---

Lot #	Item	Nos	Specification
-------	------	-----	---------------

Lot 5	<b>Filter (ND) &amp; Neutral Density Polarizer Filter</b>	82mm Size	4	<p><b>Key Features</b></p> <p><b>2-in-1 Variable ND and CPL Functionality</b> This filter combines both a variable neutral density filter and a circular polarizer.</p> <p>The variable ND function controls incoming light, helping manage exposure and darken bright skies.</p> <p>The CPL function reduces unwanted reflections from non-metallic surfaces such as water or glass, while enhancing color saturation and contrast.</p> <p><b>No “X” Cross Artifacts</b> The filter ring uses a self-locking, continuously rotating design that provides smooth adjustment between 1 and 5 stops (ND2–ND32). This mechanism helps prevent the common “X” cross shadowing that can appear in some variable ND filters.</p> <p><b>High-Quality Optical Glass</b> Constructed using premium optical glass with 28-layer multi-coating for improved performance. The coatings provide water resistance, scratch resistance, and maintain high image clarity.</p> <p><b>True-Color Performance</b> A specialized coating process minimizes color shifts or yellowing often seen in conventional variable ND filters, allowing more accurate and natural color reproduction.</p> <p><b>Compatibility Notice</b> Designed for lenses with an 82mm filter thread. Always check the thread marking on your lens (indicated by the “ø” diameter symbol). Requires an 86mm lens cap when attached, due to the filter’s outer diameter.</p>
-------	---	-----------	---	--

			Key Features
77mm Size	4		<p><b>Dual-Function Variable ND &amp; CPL Filter</b>  This single filter combines variable neutral density control with circular polarization.</p> <p>The ND function reduces the amount of incoming light, helping balance exposure and darken bright skies.</p> <p>The CPL function minimizes reflections from non-metallic surfaces such as water and glass while enhancing color saturation and contrast.</p> <p><b>No “X” Pattern Artifacts</b>  The filter frame uses a self-locking, continuously rotating mechanism that allows smooth adjustment between 1 and 5 stops (ND2–ND32).  This design helps prevent the “X” cross shadows sometimes seen in variable ND filters.</p> <p><b>High-Clarity Optical Glass</b>  Made from premium optical glass featuring a 28-layer multi-coating that provides:</p> <ul style="list-style-type: none"> <li>Water resistance</li> <li>Scratch resistance</li> <li>Improved transmission and high-definition imaging</li> </ul> <p><b>True-Color Output With Minimal Color Shift</b>  A specialized coating process helps eliminate partial yellowing or color shifting—an issue common in some variable ND filters—allowing more accurate and natural color reproduction in both photos and video.</p> <p><b>Compatibility Notice</b>  Designed for lenses with a 77mm filter thread.  Always confirm the thread size marked on your lens beside the “ø” symbol.  Due to the filter’s outer diameter, an 82mm lens cap is required when the filter is mounted.</p>

95mm Size	1	<p><b>Key Features</b></p> <p><b>2-in-1 Variable ND and CPL Functionality</b></p> <p>A single filter integrates both a variable neutral density filter and a circular polarizer.</p> <p>The ND function controls the amount of incoming light, helping balance exposure and darken bright skies.</p> <p>The CPL function reduces reflections from non-metallic surfaces such as water and glass, while enhancing color and contrast.</p> <p><b>No “X” Cross Artifacts</b></p> <p>The filter frame uses a self-locking, continuously rotating design that allows smooth adjustment between 1 and 5 stops (ND2–ND32).</p> <p>This mechanism helps position the desired light reduction level while preventing the appearance of dark cross patterns common in some variable ND filters.</p> <p><b>High-Quality Optical Glass</b></p> <p>Crafted using premium optical glass with 28-layer multi-coating, providing water resistance, scratch resistance, and maintaining high image definition.</p> <p><b>True-Color Performance</b></p> <p>A specialized titanium-based coating minimizes color shifting or partial yellowing, ensuring accurate and natural color reproduction for both photos and videos.</p> <p><b>Compatibility Notice</b></p> <p>Designed for lenses with a 95mm filter thread.</p> <p>Confirm the correct size by checking the “ø” diameter marking on the lens.</p> <p>Due to the filter’s outer dimensions, a 105mm lens cap is needed when the filter is attached.</p>

<b>Rear filter for wide lens:</b>	<b>Rear filter for wide lens:</b>	2	<p><b>Kit Contents &amp; Specifications</b></p> <p><b>ND Filter Set</b></p> <p>Includes four solid neutral density filters designed for consistent light reduction:</p> <ul style="list-style-type: none"> <li>ND0.9 – 3 stops</li> <li>ND1.2 – 4 stops</li> <li>ND1.8 – 6 stops</li> <li>ND3.0 – 10 stops</li> </ul> <p><b>Optical Construction</b></p> <p>Made from K9 optical glass for clarity, minimal distortion, and reliable color accuracy.</p> <p><b>Multi-Coating:</b> Each filter surface features a 10-layer anti-reflection coating to reduce flare, ghosting, and internal reflections.</p> <p><b>Nano-Coating:</b> Adds a protective hydrophobic and oleophobic layer, making the filters easier to clean and more resistant to smudges, moisture, and oils.</p> <p><b>Adapter Ring</b></p> <p><b>Compatibility:</b> Designed for rear mounting on lenses with bulbous front elements, where traditional front-mounted filters cannot be used like 12–24mm f/2.8 and also compatible with the 14mm f/1.8</p> <p><b>Material:</b> Built from durable, lightweight aerospace-grade aluminum.</p> <p><b>Installation:</b> Mounts to the rear of the lens and requires removal of specific lens components during setup.</p> <p><b>Included Tools:</b> Comes with a screwdriver and dedicated mounting screws for proper installation.</p> <p><b>Usage &amp; Functional Features</b></p> <p><b>Uniform Light Reduction:</b> The ND filters reduce light evenly across the frame, enabling the use of wider apertures or slower shutter speeds in bright environments.</p> <p><b>Color Neutrality:</b> Designed to maintain accurate color without introducing unwanted tints.</p> <p><b>Creative Applications:</b> Ideal for long-exposure photography, motion blur effects, and depth-of-field control in daylight.</p> <p><b>Rear Filter System:</b> Enables filtration on lenses with bulbous front elements, where traditional front-mounted filters cannot be used.</p>
-----------------------------------	-----------------------------------	---	--

Lot #	Item	Nos	Specification
Lot 6	Lavelier mics	2	<p>Audio Quality        Bit Depth: 24-bit        Sample Rate: 48 kHz        Signal-to-Noise Ratio: &gt; 70 dB to help minimize background hiss        Maximum SPL: 115 dB for clean audio in louder environments        Frequency Response: 20 Hz – 20 kHz        Microphone Type: Integrated omnidirectional condenser capsules on each transmitter        Wireless Transmission        Transmission Technology: 2.4 GHz with Adaptive Frequency Hopping (AFH) for stable and interference-resistant performance        Operating Range: Up to 300 m (1000 ft) line-of-sight        Latency: Designed for low latency to maintain sync between audio and video        Design &amp; Dimensions        Transmitter Weight: Approx. 9 g (0.3 oz)        Form Factor: Compact, button-style design suitable for discreet placement        Mounting Options: Magnetic clips, standard back clips, and wearable necklace-style cases for flexible placement on clothing or accessories        Compatibility &amp; Controls        Receivers (Combo Configuration):        Camera-mount receiver with a 3.5mm TRS output        USB-C plug-in receiver        Lightning plug-in receiver        Supports cameras, computers, and mobile devices (iOS/Android)        Mobile App: A companion app allows control over volume levels, noise cancellation, firmware updates, and real-time status monitoring when using mobile receivers.        On-Device Controls:        Transmitter: Single button for activating Environmental Noise Cancellation (ENC) and for remote triggering of video recording on compatible smartphones        Camera Receiver: Physical knob for fine volume control and a button to switch between mono and stereo modes        Battery &amp; Charging        Transmitter Runtime: Up to 10 hours with ENC off        Camera Receiver Runtime: Up to 9 hours        Charging Case (Camera Version):        Provides approximately 40 hours total system battery life        Can fully recharge the system up to three times</p>

Full recharge time: Under 2 hours  
Power Delivery: Supports charging during operation when the receiver is powered via USB-C  
Included in the Box  
2 × Transmitters (TX)  
1 × Camera-mount Receiver (RX)  
1 × USB-C Plug Receiver  
1 × Lightning Plug Receiver  
1 × Charging Case (Camera Version)  
Cables:  
3.5mm TRS to 3.5mm TRS  
USB-A to USB-C  
USB-C to Lightning  
Accessories:  
Windscreens  
Magnetic clips  
Back clips  
Necklace-style silicone cases  
Adhesive stickers

Shotgun mics	2	<p>Compact On-Camera Supercardioid Microphone</p> <p>Acoustic &amp; Pickup Characteristics</p> <p>Acoustic Principle: Pressure-gradient electret condenser</p> <p>Polar Pattern: Supercardioid for focused pickup and reduced off-axis noise</p> <p>Frequency Range: 20 Hz – 20 kHz</p> <p>Frequency Response: 35 Hz – 18 kHz (<math>\pm 3</math> dB), optimized for speech clarity and natural detail</p> <p>Audio &amp; Electrical Performance</p> <p>Output Impedance: <math>10 \Omega</math></p> <p>Signal-to-Noise Ratio: 79 dBA</p> <p>Dynamic Range: 105 dB SPL (A-weighted, IEC651 standard)</p> <p>Equivalent Noise: 15 dB SPL (A-weighted)</p> <p>Sensitivity: <math>-26</math> dB re 1V/Pa (50 mV @ 94 dB SPL), <math>\pm 1</math> dB at 1 kHz</p> <p>Maximum Input SPL (1% THD): 120 dB SPL</p> <p>Filtering &amp; Recording Options</p> <p>High-Pass Filters: Selectable 75 Hz and 150 Hz options to reduce rumble, handling noise, and low-frequency interference</p> <p>Bit Depth: 24-bit</p> <p>Sample Rate: 48 kHz</p> <p>Power &amp; Battery</p> <p>Battery Life: 30+ hours of continuous operation</p> <p>Battery Capacity: 350 mAh rechargeable internal battery</p> <p>Connectivity</p> <p>Output Connection: 3.5 mm auto-sensing port and USB-C output, compatible with cameras, phones, and other recording devices</p>
--------------	---	--

Lot #	Item	Nos	Specification
Lot 7	Tripod type 1	2	<p>Carbon Fiber Tripod &amp; Fluid Head</p> <p>Materials &amp; Build</p> <p>Construction Material: Carbon fiber</p> <p>Color: Black</p> <p>Load &amp; Height Parameters</p> <p>Maximum Load Capacity: 5 kg</p> <p>Maximum Height: 158 cm</p> <p>Minimum Height: 55 cm</p> <p>Folded Length: 85 cm</p> <p>Tripod &amp; Head Configuration</p> <p>Leg Sections: 3</p> <p>Spreader Type: Mid-level spreader</p> <p>Pan Drag: Fixed fluid cartridge</p> <p>Tilt Drag: Fixed fluid cartridge</p> <p>Mounting &amp; Interface</p> <p>Sliding Plate Type: Long-format sliding plate (compatible with standard long quick-release systems)</p> <p>Mounting Base Diameter: 60 mm</p> <p>Included Accessories</p>

	<p>Carry bag</p> <p>Sliding plate</p> <p>Warranty</p> <p>Coverage: 2 years standard + 8-year extension</p> <p>Physical Information</p> <p>Weight: 2.7 kg</p> <p>Dimensions: 85 × 16 × 16 cm</p>
--	---

Tripod type 2	2	Load Capacity 11 lb / 5 kg Maximum Working Height 64.9" / 164.8 cm Max Height without Center Column 54.7" / 138.9 cm Minimum Working Height 2.4" / 6.1 cm Folded Length 24.7" / 62.7 cm Head Mount Type 3/8"-16 Screw Weight 3.9 lb / 1.8 kg Materials Aluminum Alloy Legs Leg Lock Type Flip Lock Leg Positions 4 Positions Independent Leg Spread Yes Leg Sections 3 Leg Diameter 1" / 25.4 mm Center Column Center Column Sections 1 Center Column Extension Type Rapid Lateral / 90-Degree Center Column Yes Packaging Info Box Dimensions (LxWxH) 26.0 x 5.0 x 5.0" MH804-3W 3-Way Pan/Tilt Head Material Technopolymer Load Capacity 8.8 lb (4 kg) Tilt Range Front: -30° / 90° Lateral: -30° / 90° Panning Range 360° Quick Release Yes, RC2 Bubble Level Yes, bull's eye Friction Control No Tripod Mount Thread Size 3/8"-16 Height 4.7" (12 cm) Weight 1.65 lb (750 g) Packaging Info Box Dimensions (LxWxH) 6.299 x 6.299 x 6.063"
------------------	---	--

Gorillapod	2	<p>Flexible Tripod Stand — Specifications</p> <p>Materials: Machined aluminum, ABS plastic, TPE, stainless steel  Load Capacity: 11 lb (5 kg)  Dimensions (Folded): 2.6 × 2.6 × 15.2 in (6.5 × 6.5 × 38.5 cm)  Weight: 17 oz (482 g)  Attachment Thread: 1/4"-20 with included 3/8"-16 adapter  Legs: Fully flexible, jointed legs with rubberized rings and grippy feet for stable positioning on uneven or irregular surfaces</p> <p>Ball Head — Specifications</p> <p>Materials: Aluminum, stainless steel, TPE, ABS plastic  Load Capacity: 11 lb (5 kg)  Dimensions: 3.3 × 2.6 × 2.6 in (8.5 × 6.5 × 6.5 cm)  Weight: 5.1 oz (144 g)  Mounting System: 1/4"-20 mount with included 3/8" adapter  Quick-Release Plate: Compatible with standard dovetail-style quick-release systems  Movement: 360° panning with a dedicated pan lock; 90° tilt capability</p>
------------	---	---

Tripod for  
CMU

2

#### General specifications

Material: The legs and construction are made of aluminum alloy for a sturdy and lightweight build. Some head components use ABS plastic.

Maximum height: 160 cm (63 inches), with a center column fully extended.

Maximum height (center column down): 131 cm.

Minimum height: 51 cm or 20.08 inches.

Folded length: 55 cm (21.7 inches).

Load capacity: Up to 6 kg or 13.2 lbs.

Net weight: 1.3 kg or 2.86 lbs.

Leg sections: 3.

Leg locks: Flip-locks for fast and efficient height adjustments.

Leg angle adjustment: Features snap-lock with an angle range of 20° to 80°.

Feet: Rubber foot pads with built-in foot pegs that can be switched for different terrains

#### Head features

Head type: Fluid pan-tilt head for smooth and precise horizontal and vertical movement.

Pan angle: 360° for panoramic shooting.

Tilt angle: 90° to -90°.

Detachable handle: The handle can be detached and switched for left- or right-hand use.

Quick release plate: Arca-Swiss type quick release plate for efficient camera installation.

Head material: The ball head is made of aluminum alloy, while other head components use ABS.

#### Compatibility and additional features

Compatible devices: DSLR cameras, mirrorless cameras, camcorders, and smartphones.

Mounting options: 1/4-20 and 3/8-16 mount types.

Included accessories: Comes with a free smartphone clamp.

Inverted center column: The central axis can be mounted inverted for low-angle macro shots.

Lot #	Item	Nos	Specification
Lot 8	Video Light	3	<p>LED Spotlight</p> <p>Key Specs</p> <p>Item Type:</p> <ul style="list-style-type: none"> <li>• 1× LED spotlight</li> </ul> <p>Included Light Modifier:</p> <ul style="list-style-type: none"> <li>• 1× Reflector</li> </ul> <p>Included Storage Case:</p> <ul style="list-style-type: none"> <li>• Yes</li> </ul> <p>Photometrics (Unmodified / With Reflector) (All readings taken at distances of 3.3 ft / 1 m, 6.6 ft / 2 m, and 9.8 ft / 3 m)</p> <p>1800K Unmodified: 952 Lux / 243 Lux / 107 Lux With Reflector: 5480 Lux / 1520 Lux / 700 Lux</p> <p>2800K Unmodified: 2700 Lux / 703 Lux / 312 Lux With Reflector: 14,800 Lux / 4110 Lux / 1910 Lux</p> <p>3200K Unmodified: 2480 Lux / 648 Lux / 288 Lux With Reflector: 13,600 Lux / 3750 Lux / 1740 Lux</p> <p>4300K Unmodified: 2430 Lux / 636 Lux / 283 Lux With Reflector: 13,300 Lux / 3690 Lux / 1710 Lux</p> <p>5600K Unmodified: 2360 Lux / 617 Lux / 275 Lux With Reflector: 12,900 Lux / 3570 Lux / 1660 Lux</p> <p>6500K Unmodified: 2320 Lux / 604 Lux / 269 Lux With Reflector: 12,600 Lux / 3500 Lux / 1620 Lux</p> <p>8500K Unmodified: 2190 Lux / 570 Lux / 254 Lux With Reflector: 11,900 Lux / 3280 Lux / 1520 Lux</p> <p>10,000K Unmodified: 2120 Lux / 549 Lux / 246 Lux With Reflector: 11,700 Lux / 3210 Lux / 1490 Lux</p> <p>Lighting Features</p> <p>Color Temperature Range:</p>

		<ul style="list-style-type: none"> <li>• 1800K – 10,000K</li> </ul> <p>Color Modes:</p> <ul style="list-style-type: none"> <li>• RGB</li> <li>• Daylight</li> <li>• Tungsten</li> </ul> <p>Color Accuracy:</p> <ul style="list-style-type: none"> <li>• CRI 95</li> <li>• TLCI 95</li> </ul> <p>Dimming:</p> <ul style="list-style-type: none"> <li>• 0–100% (via onboard controls or app control)</li> </ul> <p>Cooling System:</p> <ul style="list-style-type: none"> <li>• Active cooling fan</li> </ul> <p>Built-In Flash:</p> <ul style="list-style-type: none"> <li>• No</li> </ul> <p>Lighting Effects:</p> <ul style="list-style-type: none"> <li>• Yes (multiple preprogrammed effects)</li> </ul> <p>Umbrella Mount:</p> <ul style="list-style-type: none"> <li>• Not included</li> </ul> <p>Front Accessory Mount:</p> <ul style="list-style-type: none"> <li>• Proprietary mount</li> </ul> <p>Connectivity</p> <p>Wireless Control:</p> <ul style="list-style-type: none"> <li>• Bluetooth</li> </ul> <p>Mobile App Compatibility:</p> <ul style="list-style-type: none"> <li>• iOS &amp; Android</li> </ul> <p>Wireless Range:</p> <ul style="list-style-type: none"> <li>• Up to 30 m (98.4 ft)</li> </ul> <p>Power &amp; I/O</p> <p>Power Sources Supported:</p> <ul style="list-style-type: none"> <li>• AC to DC adapter (included)</li> <li>• V-mount battery (optional, not included)</li> <li>• NP-F-style batteries (optional, not included)</li> <li>• USB power input (cable not included)</li> </ul> <p>Inputs/Outputs:</p> <ul style="list-style-type: none"> <li>• 1× USB-C power input</li> <li>• 1× Barrel/Coax power input (20 VDC, 6 A)</li> </ul> <p>Power Consumption:</p>
--	--	---

		<ul style="list-style-type: none"> <li>• 110 W</li> </ul> <p>Included AC Adapter:</p> <ul style="list-style-type: none"> <li>• Standard AC to DC power adapter (North American plug)</li> </ul> <p>Battery Compatibility</p> <ul style="list-style-type: none"> <li>• 1× V-mount rechargeable battery or</li> <li>• 2× NP-F-type rechargeable batteries</li> </ul> <p>(Both optional, not included)</p> <p>Fixture Mounting</p> <p>Mounting Thread:</p> <ul style="list-style-type: none"> <li>• 1× 1/4"-20 female thread</li> </ul>
Powerbank holder for video light	3	<p>Compatibility      With LED spot light mentioned above</p> <p>Mount      1/4"-20 Thread</p> <p>Colour      Black</p>
Diffuser Box	3	<p>Compatibility      With LED spot light mentioned above</p> <p>Mount      1/4"-20 Thread</p> <p>Colour      Black</p>

			<p>Product Dimensions      83 x 36 x 70 cm; 3.9 Kilograms      Compatible Devices      LED Video Light, Ring Light      Mounting Hardware      2 9 feet Light Stand and Carry Bag      Number Of Items      3      Batteries Required      No      Material      Aluminium      Item Weight      3 kg 900 g</p>
	Lightstand	3	

	<p>Speedlight flash for respective camera system</p>	<p>1</p>	<p><b>Flash Unit</b> <b>Flash Performance</b></p> <p>Guide Number: 60 meters at ISO 100, measured at the 200mm zoom position (197 ft).</p> <p>Maximum Output: Approximately 76 Ws at full power (1/1).</p> <p>Flash Modes:</p> <ul style="list-style-type: none"> <li>• TTL auto-flash</li> <li>• Manual flash</li> <li>• Multi flash (stroboscopic)</li> </ul> <p>Flash Duration: Ranges from 1/300 to 1/20,000 second depending on power level.</p> <p>Color Temperature: 5600K ± 200K.</p> <p>Zoom Range: 20–200mm with auto-zoom functionality that adapts to the camera's sensor size.</p> <p>Bounce / Swivel Range:</p> <ul style="list-style-type: none"> <li>• Horizontal rotation: 0° to 330°</li> <li>• Vertical tilt: -7° to 120°</li> </ul> <p><b>Power System &amp; Recycling</b></p> <p>Battery Type: 7.2V, 2600mAh rechargeable lithium-ion battery.</p> <p>Approximate Capacity: Up to 480 full-power flashes on a full charge.</p> <p>Recycle Time: About 1.5 seconds at full power.</p> <p>Battery Compatibility: Designed for this flash unit; interchangeable with batteries of similar size and voltage</p> <p><b>Additional Features</b></p> <p>Modeling Light: Integrated 2W LED with 10 adjustable brightness levels.</p>
--	--	----------	---

		<p>Quick Mode Switch: Side button for instant switching between TTL and Manual shooting modes.</p> <p>Mounting Lock: Quick-release lever-style locking mechanism for fast and secure attachment to a camera hot shoe.</p> <p>Sync Options:</p> <ul style="list-style-type: none"><li>• High-Speed Sync (up to 1/8000s)</li><li>• First-curtain sync</li><li>• Second-curtain sync</li></ul>
--	--	---

			<p>Universal Flash Modifier Kit Included Components Magnetic Silicone Base</p> <p>A slim, lightweight silicone mount that attaches securely to a flash head using strong neodymium rare-earth magnets. Designed for universal compatibility with most rectangular flash heads.</p> <p>Soft Omni-Directional Dome</p> <p>A flexible, silicone dome diffuser that converts harsh flash output into a soft, bare-bulb style light. This updated version is approximately 40% lighter than earlier-generation domes.</p> <p>Bounce Modifier</p> <p>A large bounce accessory that increases the effective surface area of the flash by up to 300%, resulting in a softer and more evenly spread light. This version is around 30% lighter than previous designs and can be folded for easier storage.</p> <p>Grid Modifier</p> <p>A magnetic grid that restricts light spill and tightens the beam into a more controlled, directional pattern—ideal for highlighting subjects without illuminating the background.</p> <p>Color Correction Gel Set</p> <p>A collection of six color-correction gels, each embedded with magnets for quick and secure attachment to the flash modifier system. These gels allow fast color balancing and creative control.</p>
Speedlight diffuser kit	1		

			<p>Rechargeable Flash Battery Electrical &amp; Capacity</p> <p>Capacity: 2600mAh (or 3000mAh in newer variants)</p> <p>Voltage: 7.2V</p> <p>Energy:</p> <p>18.72Wh for the 2600mAh version</p> <p>21.6Wh for the 3000mAh version</p> <p>Compatibility : Must be compatible with mentioned Speedlight(Flash Unit)</p> <p>Battery Type: Rechargeable lithium-ion</p> <p>Flash Performance</p> <p>Full-Power Output Per Charge: Up to approximately 480 full-power flashes</p> <p>Compatibility : Must be compatible with previously mentioned speedlight.</p>
Speedlight Battery	2		

Speed light trigger	1	<p>Wireless Flash Trigger Core Wireless Functions</p> <p>System compatibility: Operates within a 2.4GHz wireless flash control ecosystem and can control on-camera flashes, portable flashes, and studio strobes within the same system.</p> <p>Wireless range: Approx. 328 ft (100 m).</p> <p>Wireless IDs: Offers 99 wireless ID options in addition to 32 channels to minimize interference from nearby devices.</p> <p>Channel scanning: An auto-scan feature detects and selects the channel with the least interference for stable communication.</p> <p>Group control: Supports control of five independent groups (A, B, C, D, E).</p> <p>Flash Sync and Exposure</p> <p>Supported modes: TTL automatic flash, manual flash, and multi-flash (stroboscopic).</p> <p>High-Speed Sync: Enables shutter speeds up to 1/8000 s.</p> <p>Second-curtain sync: Triggers the flash at the end of the exposure.</p> <p>Flash exposure compensation (FEC): Adjustable <math>\pm 3</math> stops in 1/3-stop increments.</p> <p>Flash exposure lock (FEL): Locks the calculated flash output for re-framing.</p> <p>Minimum manual power: Down to 1/256, adjustable in 0.1-stop increments.</p> <p>TCM function: Converts a TTL-determined output value into an equivalent manual power setting.</p> <p>Design and Interface</p> <p>Display: Large, backlit LCD for visibility in low-light environments.</p>
---------------------	---	---

		<p>Controls: Five dedicated group buttons and a repositioned control dial for quick adjustments.</p> <p>Hotshoe mount: Features a quick-locking mount for secure attachment.</p> <p>AF assist light: Uses a visible-light focus-assist beam to help autofocus in dim conditions.</p> <p>Connectivity and Power</p> <p>Bluetooth: Built-in Bluetooth enables remote flash control through a mobile device app.</p> <p>USB-C port: For firmware updates.</p> <p>3.5mm sync port: Allows wired triggering from cameras or other sync sources.</p> <p>Power source: Powered by two AA batteries.</p> <p>Memory function: Automatically restores previously used settings after powering off and on.</p>
--	--	---

Lot #	Item	Nos	Specification
Lot 9	Camera Cage	2	<p>Camera Cage — Specifications</p> <p>Support Type</p> <p>Camera cage</p> <p>Grip Type</p> <p>None</p> <p>Camera Compatibility</p> <p>Full-frame mirrorless bodies as mentioned previously.</p> <p>Mounting</p> <p>Battery Plate</p> <p>None</p> <p>Accessory Mounting</p> <p>Multiple 1/4"-20 threaded holes</p> <p>Multiple 3/8"-16 threaded holes with anti-twist locating points</p> <p>Camera Mounting</p> <p>1/4"-20 screw</p> <p>Tripod Mounting</p> <p>Flat base with multiple 1/4"-20 and 3/8"-16 threaded mounting points</p> <p>Shoe Mounting</p> <p>2 × cold shoe mounts</p> <p>Rosettes</p> <p>None</p> <p>Rail Mounting</p> <p>One integrated sliding accessory rail</p> <p>General</p> <p>Materials: Aluminum, rubber, silicone, steel</p> <p>Dimensions: 5.7 × 4.2 × 2.5" (146 × 107.6 × 64.5 mm)</p> <p>Weight: 6.7 oz (190 g)</p> <p>Packaging</p> <p>Package weight: 0.58 lb</p> <p>Box: 7.2 × 5.7 × 2.8"</p> <p>HDMI Cable Clamp — Specifications</p> <p>Construction</p> <p>Aluminum</p> <p>Mounting</p> <p>1 × 1/4"-20 screw</p>

2 × anti-twist locating pins  
Cable secured with a 1/4"-20 knurled thumbscrew  
Dimensions & Weight  
1.5 × 1.2 × 1.1" (38 × 31 × 29.5 mm)  
1.2 oz (34 g)  
Packaging  
Package weight: 0.09 lb  
Box: 5.2 × 4.25 × 1.2"  
Top Handle — Specifications  
Item Type  
Top-mounted carrying handle  
Attachment Method  
Fastens with a single 3/8"-16 screw with anti-twist locating points  
Rod Compatibility  
Supports one 15 mm rod via a rod port  
Accessory Mounting  
Multiple 1/4"-20 threaded holes  
Multiple 3/8"-16 threaded holes with anti-twist locating points  
Shoe Mounts  
3 × cold shoe slots  
Rosettes  
None  
Rail Mounting  
None  
Built-In Controls  
None  
Materials  
Aluminum, steel  
Dimensions & Weight  
5.3 × 2.7 × 1" (134 × 69 × 24.5 mm)  
6.4 oz (181 g)  
Packaging  
Package weight: 0.425 lb  
Box: 6.3 × 3.1 × 1.7"  
Universal Side Handle — Specifications  
Item Type  
Ambidextrous side handgrip

	<p>Attachment Method Secures using a 3/8"-16 screw with anti-twist locating points</p> <p>Accessory Mounting 4 × 1/4"-20 threaded holes</p> <p>Shoe Mounts 1 × cold shoe slot</p> <p>Rosettes None</p> <p>Rail Mounting None</p> <p>Built-In Controls None</p>
--	--

Gimbal with accessories	2	<p><b>3-Axis Camera Stabilizer — Core Specifications</b></p> <p><b>Payload &amp; Performance</b></p> <p><b>Payload capacity:</b> Up to 4.5 kg (10 lbs)</p> <p><b>Stabilization:</b> Advanced fourth-generation stabilization algorithm with a 20% motor-torque increase for improved balance and resistance to shake</p> <p><b>Construction:</b> Carbon-fiber axis arms with low-friction, Teflon-coated components for smoother, easier balancing</p> <p><b>Rotation ranges:</b></p> <ul style="list-style-type: none"> <li>Pan: 360° continuous rotation</li> <li>Roll: -95° to +240°</li> <li>Tilt: -112° to +214°</li> </ul> <p><b>Design &amp; Operation</b></p> <p><b>Weight:</b> Approx. 1.24 kg (2.74 lbs) for the stabilizer body</p> <p><b>Dimensions:</b></p> <ul style="list-style-type: none"> <li>Folded: 271 × 283 × 75 mm</li> <li>Unfolded: 416 × 223 × 202 mm</li> </ul> <p><b>Native vertical shooting:</b> Built-in mechanism allows switching between horizontal and vertical orientation without additional accessories</p> <p><b>Axis locks:</b> Automated axis-locking system enables instant startup, shutdown, or sleep mode without manual adjustment</p> <p><b>Display:</b> 1.8" OLED touchscreen with an auto-lock function to prevent accidental menu inputs and save battery</p> <p><b>Power &amp; Connectivity</b></p> <p><b>Battery grip:</b></p> <p><b>Runtime:</b> Up to 13 hours</p> <p><b>Supports 18W PD fast charging</b></p> <p><b>Full charge time:</b> ~1.5 hours</p> <p><b>Wireless control:</b></p> <p>Bluetooth 5.1 for cable-free camera control</p> <p><b>Ports:</b></p> <ul style="list-style-type: none"> <li>Multiple universal accessory ports</li> <li>Multiple USB-C ports for control, power, and accessory integration</li> </ul> <p><b>App compatibility:</b> Connects to a companion mobile app for controls, settings, stabilization tuning, and intelligent shooting modes</p> <p><b>Combo Kit Features</b></p> <p><b>Wireless Video System</b></p> <p>Enables real-time wireless video transmission to a smartphone or tablet</p>
-------------------------	---	---

		<p>Allows remote gimbal control, camera control, and smartphone-based motion-controller operation</p> <p>Advanced Lens-Control Motor</p> <p>High-precision motor for remote focus and zoom adjustment</p> <p>Uses LiDAR-based distance detection with 76,800 ranging points</p> <p>Provides fast, intelligent autofocus within a range of up to 20 meters</p> <p>Dual-motor setup supported for simultaneous focus (dial) and zoom (joystick) operation</p> <p>Combo Kit Box Contents</p> <p>3-Axis Stabilizer</p> <p>Battery Grip</p> <p>Briefcase-Style Side Handle</p> <p>Metal Extended Grip / Tripod</p> <p>Wireless Video Transmitter</p> <p>High-Precision Lens-Control Motor</p> <p>Quick-Release Plate</p> <p>Lower Quick-Release Plate</p> <p>Lens-Support Bracket</p> <p>Smartphone Holder</p> <p>Motor Rod-Mount Kit</p> <p>Focus Gear Strip</p> <p>Cables:</p> <p>Multi-Camera Control Cable</p> <p>USB-C Charging Cable</p> <p>HDMI Cable</p> <p>Screw Kit</p> <p>Carrying Case</p>
Screen Protector	6	<p>Custom design provides full-screen coverage with edge-to-edge protection.</p> <p>Crafted from extra-strong tempered glass.</p> <p>Maintains the clarity and color of the touchscreen.</p> <p>Upgraded Protector Application Kit for easy, bubble-free installation.</p>

POV Chest Mount	6	<p>Capture immersive first-person shots completely hands-free. Maximize your POV with a huge 170° field of view in Single-Lens Mode's FreeFrame Video.</p> <p>Built for off-road or off-piste. Perfect for mountain biking, motocross, skiing, and more, for stable shots you can trust.</p> <p>Lightweight, non-slip, and adjustable for a secure and comfortable fit.</p> <p>Designed for airflow and noise reduction, get crystal-clear audio even at high speeds.</p> <p>For road cycling or motorcycling, the Chest Strap is recommended for a better shooting angle.</p>
Utility Frame	6	<p>Full-metal frame provides all-round protection.</p> <p>22% lighter than the previous generation Frame without compromising on durability.</p> <p>Features a quick release mounting point, two cold shoe mounts and two 1/4" mounting points.</p> <p>Premium quality Mic Windshields ensure clear audio capture in windy conditions or during high-speed activities.</p>
USB C Power delivery Cable	4	<p>240W USB-C to USB-C Charging Cable</p> <p><b>Key Specifications</b></p> <p><b>Power Delivery:</b> Supports up to 240W with PD 3.1 fast-charging technology, suitable for high-power devices including laptops.</p> <p><b>Data Transfer Speed:</b> 480 Mbps (USB 2.0).</p> <p>Optimized primarily for charging; not intended for high-speed data transfer or video output/screen mirroring.</p> <p><b>Connector Type:</b> USB-C male to USB-C male.</p> <p><b>Cable Construction:</b> Braided exterior with a dirt-resistant nano-coating for added durability and longevity.</p> <p><b>Durability Rating:</b> Tested to withstand 10,000+ bends.</p> <p><b>Slim Connector Profile:</b> Ultra-thin 5.8 mm connector designed to fit through most protective device cases.</p> <p><b>Cable Length:</b> 6 ft (1.8 m).</p> <p><b>Color:</b> Black.</p> <p><b>Device Compatibility</b></p> <p>Compatible with a wide range of USB-C devices, including:</p> <p>Smartphones</p> <p>Latest USB-C smartphones (e.g., recent iPhone models and Android devices).</p> <p>Laptops</p> <p>USB-C powered laptops, including models that support high-wattage fast charging.</p> <p>Tablets</p> <p>USB-C tablets such as professional tablet models and other devices with USB-C charging ports.</p>

Storage unit for Gear	2	<p><b>Dry Cabinet</b></p> <p><b>Capacity</b></p> <p>Total volume: 250 liters</p> <p><b>Humidity Control</b></p> <p>Adjustable humidity range: 25% to 60% RH</p> <p>Hygrometer accuracy: <math>\pm 5\%</math></p> <p><b>Display</b>: Digital humidity and status display</p> <p><b>Dehumidification method</b>:</p> <p>Thermoelectric cooling system</p> <p>Fast, quiet operation</p> <p>Produces no heat during dehumidification</p> <p><b>Safety &amp; Power</b></p> <p>Power input: DC power for enhanced electrical safety</p> <p>Electrical protection: Reduces risk of leakage and fire</p> <p>Energy efficiency: Suitable for continuous operation in bedrooms, studios, or offices</p> <p><b>Design &amp; Storage</b></p> <p>Item weight: 34.5 kg</p> <p><b>Shelving</b>:</p> <p>Adjustable shelves for customizable internal layout</p> <p>Supports easy organization and retrieval</p> <p><b>Door</b>:</p> <p>Toughened glass front door</p> <p>Magnetic sealing for airtight closure and humidity stability</p> <p><b>Key Protection Features</b></p> <p>Shields stored items from:</p> <ul style="list-style-type: none"> <li>Mold</li> <li>Fungus</li> <li>Dust</li> <li>Rust</li> <li>Oxidation</li> </ul> <p><b>Instant operation</b>: Starts dehumidifying as soon as power is supplied</p> <p><b>Included accessories</b>: Adapter, user manual, and foam pads for cushioning items inside</p> <p><b>Applications</b></p> <p>Ideal for long-term preservation of:</p> <ul style="list-style-type: none"> <li>Camera bodies, lenses, drones, and optical gear</li> <li>Collectibles and antiques</li> <li>Musical instruments and wooden items</li> </ul>
-----------------------	---	--

	<p>Paintings, artwork, and documents Electronic components, boards, and precision instruments</p>
--	---

3.5mm In ear earphones	2	<p>In-Ear Wired Earphone</p> <p>Acoustic &amp; Transducer</p> <p>Ear coupling: In-ear (ear canal)</p> <p>Transducer principle: Dynamic</p> <p>Transducer size: 7 mm</p> <p>Acoustic design: Closed-back</p> <p>Connectivity</p> <p>Plug type: 3.5 mm angled connector</p> <p>Cable length: 1.2 m</p> <p>Physical</p> <p>Weight: 4 g</p> <p>Audio Performance</p> <p>Frequency response: 6 Hz – 20,000 Hz</p> <p>Impedance: 16 <math>\Omega</math> (earpiece only) / 18 <math>\Omega</math> (with cable)</p> <p>Sound pressure level (SPL): 119 dB (1 kHz, 1 Vrms)</p> <p>Total harmonic distortion (THD): &lt; 0.08%</p>

Camera cleaning Kit	4	<p><b>Optical Cleaning Kit</b></p> <p><b>Key Features</b></p> <p>Complete cleaning kit for optical surfaces</p> <p>Non-abrasive microfiber cloth</p> <p>Includes both wet and dry cleaning tools</p> <p><b>Overview</b></p> <p>This comprehensive optical cleaning kit is designed for safely maintaining precision optics, including camera lenses, eyeglasses, binoculars, telescopes, and spotting scopes.</p> <p><b>Dry Cleaning Tools</b></p> <p><b>Air Blower:</b></p> <p>A manual air blaster is included for removing loose dust and debris without touching the optical surface.</p> <p><b>Retractable Cleaning Brush:</b></p> <p>A retractable, soft-bristle brush (lipstick-style) helps lift more persistent surface particles before wet cleaning.</p> <p><b>Wet Cleaning Tools</b></p> <p><b>Cleaning Fluid:</b></p> <p>One 1 oz bottle of lens-safe cleaning solution is provided for thorough wet cleaning.</p> <p><b>Pre-Moistened Cleaning Wipes:</b></p> <p>Ten individually wrapped, disposable wet wipes allow for convenient, on-the-go cleaning.</p> <p>These single-use packets can be stored in a camera bag, glove box, studio, or lens case for quick access when needed.</p> <p><b>Microfiber Cloth</b></p> <p>Size: 7.1 x 7.1 in (18 x 18 cm)</p> <p>Material: Non-abrasive microfiber suitable for delicate optical coatings</p> <p>Ideal for finishing the cleaning process to eliminate streaks or residue.</p> <p>Can also be used dry for removing fingerprints and smudges.</p> <p><b>Carrying Case</b></p> <p>Soft fabric travel pouch included to keep the entire kit organized and protected during transport.</p>
---------------------	---	--



# MEGHALAYA BASIN DEVELOPMENT AUTHORITY

(MBDA)

Office of the State Project Management Unit, MegARISE,  
RDL Building, Springside, Lumsohphoh, Nongthymmai, Shillong,  
Meghalaya – 793014.



Website: <https://megarise.in/>

Email: [megarise.spmu24@gmail.com](mailto:megarise.spmu24@gmail.com)

## Section X: Conditions of Contract

### 1. Definitions

- 1.1 In this contract, the following terms shall be interpreted as indicated:
  - a) "The Contract" means the agreement entered into between the Purchaser and the Supplier, as recorded in the Contract Form Signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein;
  - b) "The Contract Price" means the price payable to the Supplier under the contract for the full and proper performance of its contractual obligation;
  - c) "The Goods" means Equipment and related Accessories and spare-parts which the Supplier is required to supply to the Purchaser under the contract;
  - d) "Services" means services ancillary to the supply of the goods such as transportation and insurance including the installation, commissioning and the operational and maintenance training of the supplied equipment.
  - e) "The Purchaser" means the organization purchasing the goods;
  - f) "The Supplier" means the individual or firm supplying the goods and services under this contract.

### 2. Technical Specification

- 2.1 The goods supplied under this contract shall conform to the standards mentioned in the Technical Specification.

### 3. Patent Right

- 3.1 The Supplier shall indemnify the Purchaser against all third-party claims of infringement of patent, trademark or industrial design rights arising from use of goods or any part thereof in the Purchaser's country.

### 4. Inspection and Tests

- 4.1 The Purchaser or its Representative shall have the right to inspect and/or test the goods to confirm their conformity to the Technical Specification and the quality of performance after the supply and delivery of good to Purchaser's premises.
- 4.2 Should any inspected goods fail to conform to the specifications, the Purchaser may reject them and the Supplier shall either replace the rejected Goods or make all alterations necessary to meet specification requirements free to the Purchaser.

### 5. Packing

- 5.1 The Supplier shall provide such packing of the goods as is required to prevent their damage or deterioration during transit to their final destination as indicated in the contract.



# MEGHALAYA BASIN DEVELOPMENT AUTHORITY

(MBDA)

Office of the State Project Management Unit, MegARISE,  
RDL Building, Springside, Lumsohphoh, Nongthymmai, Shillong,  
Meghalaya – 793014.



Website: <https://megarise.in/>

Email: [megarise.spmu24@gmail.com](mailto:megarise.spmu24@gmail.com)

- 5.2 The packing shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit and open storage.
- 5.3 Packing case, size and weights shall take into consideration, where appropriate, the remoteness of the goods' final destination and the absence of heavy handling facilities at all points in transit.
- 5.4 The packing, marking and documentation within and outside the packages shall comply strictly with such special requirements as shall be expressly provided in accordance with international standard and practice.

## 6. Delivery of Goods

- 6.1 Delivery of the goods shall be made by the Supplier in accordance with the terms specified by the Purchaser in its schedule of requirements.

All Goods and Related Services to be supplied under the Contract and financed by the KfW shall have their origin in accordance with Section IV (Eligibility Criteria) of the Request for Quotation.

For the purpose of this Clause, the term “goods” includes commodities, raw material, machinery, equipment, and industrial plants; and “related services” includes services such as insurance, installation, training, and initial maintenance. The term “origin” means the country where the goods have been grown, mined, cultivated, produced, manufactured, or processed; or through manufacture, processing, or assembly, another commercially recognized article results that differs substantially in its basic characteristics from its components.

## 7. Insurance

- 7.1 The goods supplied under the contract shall be fully insured in the currency of the bid price against loss or damage incidental to manufacture or acquisition, transportation, storage and delivery in the manner specified.

- 7.2 Where delivery of the goods is required by the Purchaser on a CIF or CIP basis to a specified destination, the Supplier shall arrange and pay for insurance, naming the Purchaser as the Beneficiary and the Supplier shall be required to meet all transport and storage expenses until delivery.

## 8. Warranty

- 8.1 The Supplier warrants that all the goods supplied under the contract shall fully comply with the specification laid down in the contract.
- 8.2 The Supplier warrants that the Goods supplied under the Contract are new, unused, of the most recent or current models and incorporate all recent improvements in design and materials unless



# MEGHALAYA BASIN DEVELOPMENT AUTHORITY

(MBDA)

Office of the State Project Management Unit, MegARISE,  
RDL Building, Springside, Lumsohphoh, Nongthymmai, Shillong,  
Meghalaya – 793014.



Website: <https://megarise.in/>

Email: [megarise.spmu24@gmail.com](mailto:megarise.spmu24@gmail.com)

provided otherwise in the Contract.

8.3 The following time limit for warranty shall apply:  
Standard Warranty: Transfer of the manufacturer's normal warranty conditions and time (usually 6 months to 2 years) on materials, tools and simple machinery to the Purchaser, and representation of the Purchaser is case of warranty claims.

8.4 The Purchaser shall promptly notify the Supplier in writing of any claims arising under this warranty.

8.5 Upon receipt of such notice, the Supplier shall, within 30 days replace the defective goods without cost to the Purchaser. The Supplier will be required to remove, at its own risk and cost, the defective goods.

**9. Payment**

9.1 Payment for goods supplied from within 30 days shall be made in Indian Rupees into the bank accounts of the selected supplier after the delivery, installation and commissioning of goods to the satisfaction of the Purchaser.

9.2 The Supplier's request(s) for payment shall be made to the Purchaser in writing, accompanied by the invoice describing, as appropriate, the Goods delivered and by the shipping documents and, upon fulfilment of other obligations stipulated in the Contract.

9.3 Payment shall be made promptly by the Purchaser within thirty (30) days of submission of an invoice/claim by the Supplier.

**10. Prices**

10.1 Prices charged by the Supplier for goods delivered under the contract shall not vary from the prices quoted by the Supplier in its sealed quotation.

**11. Liquidated Damages**

11.1 If the Supplier fails to deliver any or all of the goods within the time period specified in the contract, the Purchaser shall, without prejudice to its other remedies under the contract, deduct from the contract price, as liquidated damages, a sum equivalent to 1.0 percent of the contract price of delayed goods for each week of delay until actual delivery, up to a maximum deduction of 10 percent of the delayed goods' contract price. Once the maximum is reached, the Purchaser may consider termination of the contract.

**12. Resolution of Disputes**

12.1 The Purchaser and Supplier shall make every effort to resolve amicably by direct informal negotiation any disagreement or dispute arising between them under or in connection with the contract.



# MEGHALAYA BASIN DEVELOPMENT AUTHORITY

(MBDA)

Office of the State Project Management Unit, MegARISE,  
RDL Building, Springside, Lumsohphoh, Nongthymmai, Shillong,  
Meghalaya – 793014.



Website: <https://megarise.in/>

Email: [megarise.spmu24@gmail.com](mailto:megarise.spmu24@gmail.com)

---

<p><b>13. Language</b></p> <p><b>14. Applicable Law</b></p> <p><b>16. Taxes and Duties</b></p> <p><b>18. Insurance, Reimbursements, guarantee or similar claimable payments</b></p> <p><b>19. Fraud and Corruption</b></p>	<p>12.2 If, after thirty (30) days from the commencement of such informal negotiation, the Purchaser and Supplier have been unable to resolve amicably a contract dispute, it shall be referred by either party to an adjudicator agreed by the parties. In the event of disagreement, the adjudicator shall be appointed in accordance with the Laws and Rules of Purchaser's Country.</p> <p>13.1 The Governing Language of this contract shall be English.</p> <p>14.1 The applicable law shall be the Law of Purchaser's Country.</p> <p>16.1 The Supplier shall be entirely responsible for all taxes, duties, license fees and other such levies imposed by the Government of Meghalaya.</p> <p>16.2 All taxes, duties, license fees and other such levies are to be listed <b>separately</b> on the invoices.</p> <p>18.1 Any reimbursements guarantee or similar claimable payments and any insurance payments shall be remitted to a special account of the Recipient in the country of the Recipient, which may be drawn on only with the consent of KfW. Such funds may be re-utilized for the execution of the Project with KfW's consent.</p> <p>19.1 The Government requires that the Employer, as well as Bidders and Contractors shall observe the highest standard of ethics during the implementation of procurement proceedings and the execution of contracts under public funds. KfW requires the same complemented by Section IVa KfW Policy.</p> <p>19.2 In pursuance of this requirement, the Employer shall:</p> <ul style="list-style-type: none"><li>a) exclude the Bidder from participation in the procurement proceedings concerned or reject a quotation/bid for award;</li><li>b) if it, at any time, determines that the Bidder has engaged in corrupt, fraudulent, collusive or coercive practices in competing for, or in executing, a contract under public funds.</li></ul> <p>19.3 Should any corrupt, fraudulent, collusive or coercive practice of any kind come to the knowledge of the Employer, it shall, in the first place, allow the Bidder to provide an explanation and shall, take actions only when a satisfactory explanation is not received. Such exclusion and the reasons thereof, shall be recorded in the record of the procurement proceedings and promptly communicated to the Bidder concerned. Any communications between the Bidder and the Employer related to matters of alleged fraud or corruption shall be in writing.</p> <p>19.4 The Government defines, for the purposes of this provision, the terms set forth below as follows:</p>
--	---



# MEGHALAYA BASIN DEVELOPMENT AUTHORITY

(MBDA)

Office of the State Project Management Unit, MegARISE,  
RDL Building, Springside, Lumsohphoh, Nongthymmai, Shillong,  
Meghalaya – 793014.



Website: <https://megarise.in/>

Email: [megarise.spmu24@gmail.com](mailto:megarise.spmu24@gmail.com)

- a) **“Corrupt Practice”** means offering, giving, or promising to give, directly or indirectly, to any officer or employee of a Procuring Entity or other governmental/private authority or individual, a gratuity in any form, an employment, or any other thing or service of value, as an inducement with respect to an act or decision of, or method followed by, a Procuring Entity in connection with the procurement proceeding;
- b) **“Fraudulent Practice”** means a misrepresentation or omission of facts in order to influence a procurement proceeding or the execution of a contract to the detriment of the Purchaser;
- c) **“Collusive Practice”** means a scheme or arrangement among two or more Bidders, without the knowledge of the Purchaser (prior to or after Bid submission), designed to establish Bid prices at artificial, non-competitive levels and to deprive the Purchaser of the benefits of free, open and genuine competition; and
- d) **“Coercive Practice”** means harming or threatening to harm, directly or indirectly, persons or their property to influence the procurement proceedings, or affect the execution of a contract.
- e) **“Obstructive Practice”** is
  - 1) deliberately destroying, falsifying, altering or concealing of evidence material to the investigation or making false statements to investigators in order to materially impede the Government investigation into allegations of a corrupt, fraudulent, coercive or collusive practice; and/or threatening, harassing or intimidating any party to prevent it from disclosing its knowledge of matters relevant to the investigation or from pursuing the investigation, or
  - 2) acts intended to materially impede the exercise of the Government’s inspection and audit rights.

19.5 The Government requires that the Employer’s personnel have an equal obligation not to solicit, ask for and/or use coercive methods to obtain personal benefits in connection with the said proceedings.

## 20. Inspections and Audit by the KfW

- 20.1 The Supplier shall keep, and shall make all reasonable efforts to cause its Subcontractors to keep accurate and systematic accounts and records, in respect of the Goods in such form and details as will clearly identify relevant time changes and costs.
- 20.2 The Supplier shall permit, and shall cause its Subcontractors and consultants to permit, the KfW and/or persons appointed by the KfW to inspect the Supplier’s offices and all accounts and records



# MEGHALAYA BASIN DEVELOPMENT AUTHORITY

(MBDA)

Office of the State Project Management Unit, MegARISE,  
RDL Building, Springside, Lumsohphoh, Nongthymmai, Shillong,  
Meghalaya – 793014.



Website: <https://megarise.in/>

Email: [megarise.spmu24@gmail.com](mailto:megarise.spmu24@gmail.com)

relating to the performance of the Contract and the submission of the bid, and to have such accounts and records audited by auditors appointed by the KfW if requested by the KfW.

## 21. Force Majeure

- 21.1 The Supplier shall not be liable for forfeiture of its Performance Security, liquidated damages, or termination for default if and to the extent that it's delay in performance or other failure to perform its obligations under the Contract is the result of an event of Force Majeure.
- 21.2 For purposes of this Clause, "Force Majeure" means an event or situation beyond the control of the Supplier that is not foreseeable, is unavoidable, and its origin is not due to negligence or lack of care on the part of the Supplier. Such events may include, but not be limited to, acts of the Purchaser in its sovereign capacity, wars or revolutions, fires, floods, epidemics, quarantine restrictions, and freight embargoes.
- 21.3 If a Force Majeure situation arises, the Supplier shall promptly notify the Purchaser in writing of such condition and the cause thereof. Unless otherwise directed by the Purchaser in writing, the Supplier shall continue to perform its obligations under the Contract as far as is reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the Force Majeure event.

## 22. Termination

### 22.1 Termination for Default

- a) The Purchaser, without prejudice to any other remedy for breach of Contract, by written notice of default sent to the Supplier, may terminate the Contract in whole or in part:
  - (i) If the Supplier fails to deliver any or all of the Goods within the period specified in the Contract
  - (ii) If the Supplier fails to perform any other obligation under the Contract
  - (iii) If the Supplier, in the judgment of the Purchaser has engaged in fraud and corruption.
- b) In the event the Purchaser terminates the Contract in whole or in part, pursuant to Clause 21.1(a), the Purchaser may procure, upon such terms and in such manner as it deems appropriate, Goods or Related Services similar to those undelivered or not performed, and the Supplier shall be liable to the Purchaser for any additional costs for such similar Goods or Related Services. However, the Supplier shall continue performance of the Contract to the extent not terminated.

### 22.2 Termination for Insolvency



## MEGHALAYA BASIN DEVELOPMENT AUTHORITY

(MBDA)

Office of the State Project Management Unit, MegARISE,  
RDL Building, Springside, Lumsohphoh, Nongthymmai, Shillong,  
Meghalaya – 793014.



Website: <https://megarise.in/>

Email: [megarise.spmu24@gmail.com](mailto:megarise.spmu24@gmail.com)

---

- a) The Purchaser may at any time terminate the Contract by giving notice to the Supplier if the Supplier becomes bankrupt or otherwise insolvent. In such event, termination will be without compensation to the Supplier, provided that such termination will not prejudice or affect any right of action or remedy that has accrued or will accrue thereafter to the Purchaser.



# MEGHALAYA BASIN DEVELOPMENT AUTHORITY

(MBDA)

Office of the State Project Management Unit, MegARISE,  
RDL Building, Springside, Lumsohphoh, Nongthymmai, Shillong,  
Meghalaya – 793014.



Website: <https://megarise.in/>

Email: [megarise.spmu24@gmail.com](mailto:megarise.spmu24@gmail.com)

## Section XI: Contract Form

THIS AGREEMENT made the \_\_\_\_\_ day of \_\_\_\_\_ 2025 between Meghalaya Basin Development Authority (MBDA) (hereinafter called "the Purchaser") of the one part and \_\_\_\_\_ (hereinafter called "the Supplier") of the other part:

WHEREAS the Purchaser invited bids for certain goods and ancillary services, viz.,

### **Procurement of Material for Knowledge Management under MegARISE**

**RFQ No.: MBDA/MegARISE/2025-26/G-17/**

and has accepted a bid by the Supplier for the supply of those goods in the sum of \_\_\_\_\_ (hereinafter called "the Contract Price").

NOW THIS AGREEMENT WITNESSES AS FOLLOWS:

1. In this Agreement words and expressions shall have the same meanings as are respectively assigned to them in the Conditions of Contract referred to.
2. The following documents shall be deemed to form and be read and construed as part of this Agreement, viz.:
  - a) Quotation Form and the Price Schedule submitted by the Supplier;
  - b) The Schedule of Requirements;
  - c) The Technical Specifications;
  - d) The Conditions of Contract; and
  - e) The Purchaser's Notification of Award.
  - f) Signed Declaration of Undertaking
3. In consideration of the payments to be made by the Purchaser to the Supplier as hereinafter mentioned, the Supplier hereby covenants with the Purchaser to provide the goods and services and to remedy defects therein in conformity in all respects with the provisions of the Contract.
4. The Purchaser hereby covenants to pay the Supplier in consideration of the provision of the goods and services and the remedying of defects therein, the Contract Price or such other sum as may become payable under the provisions of the contract at the times and in the manner prescribed by the Contract.



## MEGHALAYA BASIN DEVELOPMENT AUTHORITY

(MBDA)

Office of the State Project Management Unit, MegARISE,  
RDL Building, Springside, Lumsohphoh, Nongthymmai, Shillong,  
Meghalaya – 793014.



Website: <https://megarise.in/>

Email: megarise.spmu24@gmail.com

IN WITNESS whereof the parties hereto have caused this Agreement to be executed in accordance with their respective laws the day and year first above written.

On behalf of the Purchaser

On behalf of the Supplier

Name:

Name:

Designation:

Designation:

Sign:

Sign:

Seal:

Seal: